

Safety Data Sheet

Copyright, 2015, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	33-1471-3	Version Number:	1.01
Issue Date:	02/04/15	Supercedes Date:	03/04/14

SECTION 1: Identification

1.1. Product identifier

3MTM High Power Brake Cleaner, PN 08880

Product Identification Numbers 60-4550-8249-9, 60-4550-8252-3

1.2. Recommended use and restrictions on use

Recommended use Automotive

1.3. Supplier's details	
MANUFACTURER:	3M
DIVISION:	Automotive Aftermarket
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number 1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification

Flammable Aerosol: Category 1. Acute Toxicity (oral): Category 4. Acute Toxicity (inhalation): Category 4. Serious Eye Damage/Irritation: Category 2B. Skin Corrosion/Irritation: Category 2. Aspiration Hazard: Category 1. Reproductive Toxicity: Category 2. Carcinogenicity: Category 2. Specific Target Organ Toxicity (single exposure): Category 1. Specific Target Organ Toxicity (central nervous system): Category 3. Specific Target Organ Toxicity (repeated exposure): Category 1. 2.2. Label elements Signal word Danger

Symbols Flame | Exclamation mark | Health Hazard |

Pictograms



Hazard Statements Extremely flammable aerosol.

Harmful if swallowed. Causes eye irritation. Causes skin irritation. Harmful if inhaled. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. Suspected of causing cancer.

Causes damage to organs: cardiovascular system | sensory organs

Causes damage to organs through prolonged or repeated exposure: nervous system

sensory organs |

Precautionary Statements General:

Keep out of reach of children.

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Rinse mouth. Do NOT induce vomiting. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Specific treatment (see Notes to Physician on this label). Call a POISON CENTER or doctor/physician if you feel unwell.

Storage:

Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

Notes to Physician:

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary. This product contains methanol. Methanol poisoning can cause metabolic acidosis, blindness, and death. Onset of signs or symptoms may be delayed for 18 to 24 hours. If methanol poisoning is confirmed, intravenous (IV) administration of ethanol should be considered. Additional pharmacologic and supportive care should be based on the treating physician's judgement.

2.3. Hazards not otherwise classified

None.

15% of the mixture consists of ingredients of unknown acute oral toxicity.15% of the mixture consists of ingredients of unknown acute dermal toxicity.15% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Heptane, branched, cyclic and linear	426260-76-6	30 - 60 Trade Secret *
Xylene	1330-20-7	10 - 30 Trade Secret *
Propane	74-98-6	10 - 30 Trade Secret *
Methyl Alcohol	67-56-1	5 - 10 Trade Secret *
Ethylbenzene	100-41-4	1 - 10 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. Get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

This product contains methanol. Methanol poisoning can cause metabolic acidosis, blindness, and death. Onset of signs or symptoms may be delayed for 18 to 24 hours. If methanol poisoning is confirmed, intravenous (IV) administration of ethanol should be considered. Additional pharmacologic and supportive care should be based on the treating physician's judgement.

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

<u>Substance</u>	Condition
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Toxic Vapor, Gas, Particulate	During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Cover spill area with a fire-extinguishing foam. An appropriate aqueous film forming foam (AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow

safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Ethylbenzene	100-41-4	ACGIH	TWA:20 ppm	A3: Confirmed animal
				carcin.
Ethylbenzene	100-41-4	CMRG	TWA:25 ppm;STEL:75 ppm	
Ethylbenzene	100-41-4	OSHA	TWA:435 mg/m3(100 ppm)	
Xylene	1330-20-7	ACGIH	TWA:100 ppm;STEL:150 ppm	A4: Not class. as human
				carcin
Xylene	1330-20-7	CMRG	TWA:50 ppm;STEL:75 ppm	
Xylene	1330-20-7	OSHA	TWA:435 mg/m3(100 ppm)	
Methyl Alcohol	67-56-1	ACGIH	TWA:200 ppm;STEL:250 ppm	Skin Notation
Methyl Alcohol	67-56-1	OSHA	TWA:260 mg/m3(200 ppm)	
Propane	74-98-6	ACGIH	Limit value not established:	
Propane	74-98-6	OSHA	TWA:1800 mg/m3(1000 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Fluoroelastomer Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

it intormation on suste physical and enclinear pr	operates
General Physical Form:	Liquid
Specific Physical Form:	Aerosol
Odor, Color, Grade:	Clear colorless; Solvent odor
Odor threshold	No Data Available
рН	Not Applicable
Melting point	No Data Available
Boiling Point	No Data Available
Flash Point	>=-156 °F
Evaporation rate	No Data Available
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	No Data Available
Flammable Limits(UEL)	No Data Available
Vapor Pressure	40 psi [@ 70 °F]
Vapor Density	>=1.0 [<i>Ref Std:</i> AIR=1]
Density	0.699 g/ml
Specific Gravity	0.699 [<i>Ref Std:</i> WATER=1]
Solubility in Water	Nil
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Viscosity	No Data Available
Hazardous Air Pollutants	34.72 % weight [Test Method: Calculated]
Volatile Organic Compounds	699 g/l [Test Method: calculated SCAQMD rule 443.1]
Volatile Organic Compounds	100 % weight [<i>Test Method:</i> calculated per CARB title 2]
Percent volatile	100 % weight
VOC Less H2O & Exempt Solvents	699 g/l [Test Method: calculated SCAQMD rule 443.1]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions Hazardous polymerization will not occur.

10.4. Conditions to avoid Heat Sparks and/or flames

10.5. Incompatible materials Strong acids Strong oxidizing agents

10.6. Hazardous decomposition products Substance

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Harmful if inhaled. Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

May be harmful in contact with skin. Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. May cause additional health effects (see below).

Eye Contact:

Condition

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Harmful if swallowed. Chemical (Aspiration) Pneumonitis: Signs/symptoms may include coughing, gasping, choking, burning of the mouth, difficulty breathing, bluish colored skin (cyanosis), and may be fatal.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

May cause blindness.

Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

Prolonged or repeated exposure may cause target organ effects:

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Ethylbenzene	100-41-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE 2,000 - 5,000
			mg/kg
Overall product	Inhalation-		No data available; calculated ATE 10 - 20 mg/l
	Vapor(4 hr)		
Overall product	Ingestion		No data available; calculated ATE 300 - 2,000 mg/kg
Heptane, branched, cyclic and linear	Dermal	Rabbit	LD50 > 2,000 mg/kg
Heptane, branched, cyclic and linear	Inhalation-	Rat	LC50 > 73.5 mg/l
	Vapor (4		
	hours)		
Heptane, branched, cyclic and linear	Ingestion	Rat	LD50 > 5,000 mg/kg
Xylene	Dermal	Rabbit	LD50 > 4,200 mg/kg
Xylene	Inhalation-	Rat	LC50 29 mg/l
	Vapor (4		_
	hours)		
Xylene	Ingestion	Rat	LD50 3,523 mg/kg
Propane	Inhalation-	Rat	LC50 > 200,000 ppm

	Gas (4		
	hours)		
Methyl Alcohol	Dermal		LD50 estimated to be 1,000 - 2,000 mg/kg
Methyl Alcohol	Inhalation-		LC50 estimated to be 10 - 20 mg/l
	Vapor		
Methyl Alcohol	Ingestion		LD50 estimated to be 50 - 300 mg/kg
Ethylbenzene	Dermal	Rabbit	LD50 15,433 mg/kg
Ethylbenzene	Inhalation-	Rat	LC50 17.4 mg/l
	Vapor (4		-
	hours)		
Ethylbenzene	Ingestion	Rat	LD50 4,769 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Heptane, branched, cyclic and linear	Rabbit	Mild irritant
Xylene	Rabbit	Mild irritant
Propane	Rabbit	Minimal irritation
Methyl Alcohol	Rabbit	Mild irritant
Ethylbenzene	Rabbit	Mild irritant

Serious Eye Damage/Irritation

Name	Species	Value
Heptane, branched, cyclic and linear	Rabbit	Mild irritant
Xylene	Rabbit	Mild irritant
Propane	Rabbit	Mild irritant
Methyl Alcohol	Rabbit	Moderate irritant
Ethylbenzene	Rabbit	Moderate irritant

Skin Sensitization

Name	Species	Value
Methyl Alcohol	Guinea	Not sensitizing
	pig	
Ethylbenzene	Human	Not sensitizing

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Xylene	In Vitro	Not mutagenic
Xylene	In vivo	Not mutagenic
Propane	In Vitro	Not mutagenic
Methyl Alcohol	In Vitro	Some positive data exist, but the data are not
		sufficient for classification
Methyl Alcohol	In vivo	Some positive data exist, but the data are not
		sufficient for classification
Ethylbenzene	In vivo	Not mutagenic
Ethylbenzene	In Vitro	Some positive data exist, but the data are not
		sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Xylene	Dermal	Rat	Not carcinogenic
Xylene	Ingestion	Multiple	Not carcinogenic
		animal	
		species	
Xylene	Inhalation	Human	Some positive data exist, but the data are not
			sufficient for classification
Methyl Alcohol	Inhalation	Multiple	Not carcinogenic
		animal	-

		species	
Ethylbenzene	Inhalation	Multiple animal	Carcinogenic
		species	

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Xylene	Ingestion	Not toxic to female reproduction	Mouse	NOAEL 1,000 mg/kg/day	103 weeks
Xylene	Ingestion	Not toxic to male reproduction	Mouse	NOAEL 1,000 mg/kg/day	103 weeks
Xylene	Inhalation	Some positive female reproductive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Xylene	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Mouse	NOAEL Not available	during organogenesi s
Xylene	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	during gestation
Methyl Alcohol	Ingestion	Some positive male reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,600 mg/kg/day	21 days
Methyl Alcohol	Ingestion	Toxic to development	Mouse	LOAEL 4,000 mg/kg/day	during organogenesi s
Methyl Alcohol	Inhalation	Toxic to development	Mouse	NOAEL 1.3 mg/l	during organogenesi s
Ethylbenzene	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 4.3 mg/l	premating & during gestation

Lactation

Name	Route	Species	Value
Xylene	Ingestion	Mouse	Does not cause effects on or via lactation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Heptane, branched, cyclic and linear	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL not available	
Xylene	Inhalation	auditory system	Causes damage to organs	Rat	LOAEL 6.3 mg/l	8 hours
Xylene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Xylene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Xylene	Inhalation	eyes	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 3.5 mg/l	not available
Xylene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal	NOAEL Not available	

				species		
Xylene	Ingestion	eyes	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 250 mg/kg	not applicable
Propane	Inhalation	cardiac sensitization	Causes damage to organs	Human	NOAEL Not available	
Propane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Propane	Inhalation	respiratory irritation	All data are negative	Human	NOAEL Not available	
Methyl Alcohol	Inhalation	blindness	Causes damage to organs	Human	NOAEL Not available	occupational exposure
Methyl Alcohol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	not available
Methyl Alcohol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	6 hours
Methyl Alcohol	Ingestion	blindness	Causes damage to organs	Human	NOAEL Not available	poisoning and/or abuse
Methyl Alcohol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Ethylbenzene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Ethylbenzene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Xylene	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.4 mg/l	4 weeks
Xylene	Inhalation	auditory system	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 7.8 mg/l	5 days
Xylene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	
Xylene	Inhalation	heart endocrine system hematopoietic system muscles kidney and/or bladder respiratory system	All data are negative	Multiple animal species	NOAEL 3.5 mg/l	13 weeks
Xylene	Ingestion	auditory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 900 mg/kg/day	2 weeks
Xylene	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,500 mg/kg/day	90 days
Xylene	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	heart skin endocrine system bone, teeth, nails, and/or hair hematopoietic system immune system nervous system respiratory system	All data are negative	Mouse	NOAEL 1,000 mg/kg/day	103 weeks
Methyl Alcohol	Inhalation	liver	All data are negative	Rat	NOAEL 6.55 mg/l	4 weeks
Methyl Alcohol	Inhalation	respiratory system	All data are negative	Rat	NOAEL 13.1 mg/l	6 weeks

Methyl Alcohol	Ingestion	liver nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 2,500 mg/kg/day	90 days
Ethylbenzene	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	2 years
Ethylbenzene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 1.1 mg/l	103 weeks
Ethylbenzene	Inhalation	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 3.4 mg/l	28 days
Ethylbenzene	Inhalation	auditory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 2.4 mg/l	5 days
Ethylbenzene	Inhalation	endocrine system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 3.3 mg/l	103 weeks
Ethylbenzene	Inhalation	bone, teeth, nails, and/or hair muscles	All data are negative	Multiple animal species	NOAEL 4.2 mg/l	90 days
Ethylbenzene	Inhalation	heart immune system respiratory system	All data are negative	Multiple animal species	NOAEL 3.3 mg/l	2 years
Ethylbenzene	Ingestion	liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 680 mg/kg/day	6 months

Aspiration Hazard

Name	Value
Heptane, branched, cyclic and linear	Aspiration hazard
Xylene	Aspiration hazard
Ethylbenzene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Facility must be capable of handling aerosol cans. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

Ingredient	C.A.S. No	<u>% by Wt</u>
Methyl Alcohol	67-56-1	5 - 10
Ethylbenzene	100-41-4	1 - 10
Xylene	1330-20-7	10 - 30
Xylene (Benzene, 1,2-dimethyl-)	1330-20-7	10 - 30
Xylene (Benzene, 1,3-dimethyl-)	1330-20-7	10 - 30
Xylene (Benzene, 1,4-dimethyl-)	1330-20-7	10 - 30
Xylene (Benzene, dimethyl-)	1330-20-7	10 - 30

15.2. State Regulations

Contact 3M for more information.

California Proposition 65

Ingredient	C.A.S. No.	Classification
Ethylbenzene	100-41-4	Carcinogen
Methyl Alcohol	67-56-1	Developmental Toxin

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

WARNING: This product contains a chemical known to the State of California to cause cancer.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 4 Instability: 0 Special Hazards: None Aerosol Storage Code: 3

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	33-1471-3	Version Number:	1.01
Issue Date:	02/04/15	Supercedes Date:	03/04/14

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com