

FIR No.: 175325 Level: 1

Version Number: CA-EN-5 Release Date: 2008-07-16

1. Product and Company Identification

Product Name: MERCON® SP Automatic Transmission Fluid

Product Code: See Attachment

Application:Automatic transmision fluidSupplier:Ford Motor Company of Canada

Oakville, Ontario L6J 5E4

1-800-392-3673

Emergency Telephone: Poison Control Center: 1-800-959-3673

CHEMTREC: U.S. and Canada: 1-800-424-9300 CHEMTREC: International: 1-703-527-3887

2. Composition/Information on Ingredients

This chemical product is a preparation.

Chemical Name	CAS Number	Percent Concentration	Hazard Classification
PETROLEUM DISTILLATES HYDROTREATED HEAVY PARAFFINIC	64742-54-7	60-100	HAZCOM RSMS_P_SOM
PETROLEUM DISTILLATES, HYDROTREATED HEAVY NAPHTHENIC	64742-52-5	1-5	HAZCOM RSMS_P_SOM

3. Hazards Identification

Health: May cause eye irritation.

Inhalation of vapors (generated at high temperatures only) may cause

mild irritation of the nose, throat, and respiratory tract. If ingested, this product may cause gastrointestinal irritation.

Prolonged and/or repeated skin contact with this product may cause

irritation/dermatitis.

This product may cause sensitization by skin contact.

Aspiration hazard if swallowed; can enter lungs and cause damage.

4. First-Aid Measures

Inhalation: If gas/fume/vapor/dust/mist from the material is inhaled, remove the

affected person immediately to fresh air. If irritation persists, get medical attention.

Skin Contact: Wash skin with soap and water.

If irritation persists, get medical attention.

If this material is injected beneath the skin, regardless of amount injected, get immediate medical attention. Do not wait for symptoms to

develop.

Eye Contact: In case of contact with eyes, rinse immediately with plenty of water for

at least 15 minutes and seek medical attention. If irritation persists, get medical attention.

Owner: Ford Motor Company PRINTED DOCUMENT IS TRANSIENT Ford Proprietary

Application: MATS Page: 1 / 8 Official Record



FIR No.: 175325 Level: 1

Version Number: CA-EN-5 Release Date: 2008-07-16

Ingestion: If the material is swallowed, get immediate medical attention or advice

-- Do not induce vomiting.

Notes to a Physician: HIGH PRESSURE SKIN INJECTION: Physician must be familiar with

local procedures for treatment of this type of wound; incision, irrigation,

removal of all necrotic tissue and open wound dressing.
This material, if aspirated into the lungs, may cause chemical

pneumonitis; treat the affected person appropriately.

5. Fire-Fighting Measures

Extinguishing Media: EXTINGUISHER INFORMATION: Dry chemical, foam, carbon dioxide,

water fog.

Specific Methods: Use water to cool fire-exposed containers, structures, and to protect

personnel.

Water may be an ineffective extinguishing medium.

Specific Hazards: Empty containers may retain product residue including Flammable or

Explosive vapors. Do not cut, drill, grind, or weld near full, partially full,

or empty product containers.

Protection of Firefighters: Fire fighters should be equipped with NIOSH-approved, self-contained

breathing apparatus (SCBA) and full protective clothing.

6. Accidental Release Measures

Personal Precautions: Avoid inhalation of vapors and contact with skin and eyes.

Eliminate all sources of ignition or flammables that may come into

contact with a spill of this material.

Surfaces may become slippery after spillage.

Wear appropriate protective equipment and clothing during clean-up.

Environmental Precautions:Do not allow the spilled product to enter public drainage system or

open water courses.

Methods for Cleaning Up: Absorb the spilled material with an inert absorbent (nonflammable)

material.

Scrape up the spilled material and transfer to a suitable container for

disposal.

Thoroughly wash the area after a spill or leak clean-up.

7. Handling and Storage

Handling:

Technical Measures: Keep this product from heat, sparks, or open flame.

Owner: Ford Motor Company PRINTED DOCUMENT IS TRANSIENT Ford Proprietary

Application: MATS Page: 2 / 8 Official Record



FIR No.: 175325 Level: 1

Version Number: CA-EN-5 Release Date: 2008-07-16

Precautions and Advice for Safe

Handling:

Avoid contact with skin, eyes and clothing.

Elevated temperature or mechanical action may form vapors, mist, or

fumes which may be irritating to the eyes, nose, throat, and lungs.

Avoid breathing vapors or mist.

Keep the container closed when not in use.

Storage: Technical Measures: No special precautions necessary.

Storage Conditions: Avoid prolonged exposure of the container to direct sunlight.

Store in a cool, well-ventilated area away from sources of heat.

Store this product away from strong oxidizing agents.

8. Exposure Controls/Personal Protection

Engineering Measures: ENGINEERING CONTROL: Use adequate ventilation to control

airborne concentrations below the exposure limits/guidelines. If user operations generate a vapor, dust, and/or mist, use process enclosure, local exhaust ventilation, or other engineering controls to control airborne levels below the recommended exposure limits/guidelines.

Control Parameters: If oil mist is generated, observe the OSHA exposure limit of 5 mg/m3.

Ford Motor Company recommends an exposure limit of 1.0 mg/m3.

Personal Protective Equipment:

Respiratory Protection: Explosion-proof exhaust devices are required.

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with the requirements of OSHA Respiratory Protection Standard 29 CFR 1910.134 and/or Canadian Standard

CSA Z94.4.

Hand Protection: Use of impervious gloves is required, such as neoprene or nitrile

rubber gloves.

Eye Protection: Wear safety glasses with side shields.

Wear chemical goggles; face shield (if splashing is possible).

Skin and Body Protection: Remove contaminated clothing and wash before reuse.

Hygiene Measures: Wash thoroughly after handling.

When using this material, do not eat, drink or smoke.

Owner: Ford Motor Company PRINTED DOCUMENT IS TRANSIENT Ford Proprietary
Application: MATS Page: 3 / 8 Official Record



FIR No.: 175325 Level: 1

Version Number: CA-EN-5 Release Date: 2008-07-16

9. Physical and Chemical Properties

Specific Gravity: 0.85 @15°C

Physical State: LIQUID

Odor: MINERAL OIL

Color: BROWN

pH: N.AV

Temperature Range During which Changes

in Physical State Occur:

Boiling Point: >280 °C

Flash Point: 218 °C COC

Auto-ignition Temperature: >320 °C

Explosion Properties:

UEL: 10 % LEL: 1 %

Vapor Pressure: <0.5@20°C Pa

Vapor Density: >1 (AIR=1)

Solubility: NEGLIGIBLE IN WATER

Viscosity: 28@40°C cSt

Evaporation Rate: N.AV

10. Stability and Reactivity

Stability: This is a stable material.

Conditions and Materials to Avoid: This product may react with strong oxidizing agents (bleach--sodium

hypochlorite, calcium hypochlorite, hydrogen peroxide, permanganate,

nitric acid, concentrated OXYGEN, perchlorates).

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, and other low molecular weight

hydrocarbons.

11. Toxicological Information

Chronic (Long Term) Toxicity:Base oil severely refined: Not carcinogenic in animal studies.

Representative material passes IP-346, Modified Ames test, and/or

other screening tests.

Continuous long term contact with used motor oil has caused skin

cancer in animal tests.

None of this product's components are listed by ACGIH, IARC, OSHA,

NIOSH, or NTP.

Owner: Ford Motor Company PRINTED DOCUMENT IS TRANSIENT Ford Proprietary

Application: MATS Page: 4 / 8 Official Record



FIR No.: 175325 Level: 1

Version Number: CA-EN-5 Release Date: 2008-07-16

12. Ecological Information

No specific aquatic data available for this product.

13. Disposal Considerations

Waste from Residues: Dispose of waste material according to Local, State, Federal, and

Provincial Environmental Regulation.

Contaminated Packaging: No consideration given when disposed of according to local, state, and

Federal regulations.

Owner: Ford Motor Company PRINTED DOCUMENT IS TRANSIENT Ford Proprietary
Application: MATS Page: 5 / 8 Official Record



FIR No.: 175325 Level: 1

Version Number: CA-EN-5 Release Date: 2008-07-16

14. Transport Information

U.S. Department of Transportation (DOT) 49 - CFR 172.101

This product is not regulated as a dangerous good.

Canadian Transportation of Dangerous Goods (T.D.G.) - TDGR Schedule II

This product is not regulated as a dangerous good.

Secretary of Communication and Transportation (SCT) - NOM-002-SCT2/1994 (Mexico)

This product is not regulated as a dangerous good.

International and Domestic Air Transportation - ICAO & IATA Section 4.2

This product is not regulated as a dangerous good.

International Water Transportation - IMDG Code Amendment 31-02

This product is not regulated as a dangerous good.

15. Regulatory Information

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Not a controlled product.

Don't pollute. Conserve resources. Return used oil to collection centers.

Material contains a chemical which is a Ford Motor Company Material of Concern. Use and release of this material should be minimized to the greatest extent possible.

16. Other Information

Preparation Information:

Key/Legend: N.AP = Not applicable; N.AV = Not available; ND = Not determined or No data; TLV = Threshold limit value; TWA = Time-weighted average; STEL = Short-term exposure limit; C = Ceiling limit

The following sections contain revisions OR 2

NEW statements.

15 16

The chemical identification and properties for this material were provided by the manufacturer. For Canadian locations, a manufacture's MSDS is available upon request. Health and safety information has been evaluated by the Occupational and Environmental Health Sciences Department, Ford Motor Company, Diagnostic Service Center II, 1800

Fairlane Drive, Allen Park, MI 48101, USA.

Owner: Ford Motor Company PRINTED DOCUMENT IS TRANSIENT Ford Proprietary

Application: MATS Page: 6 / 8 Official Record



FIR No.: 175325 Level: 1

Version Number: CA-EN-5 Release Date: 2008-07-16

Disclaimer:

The information on this data sheet represents our current data and is accurate to the best of our knowledge as to the proper handling of this product under normal conditions and in accordance with the application specified on the packaging and/or technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.

Owner: Ford Motor Company PRINTED DOCUMENT IS TRANSIENT Ford Proprietary
Application: MATS Page: 7 / 8 Official Record







Rotunda

Material Safety Data Sheet

175325 Level: 1 FIR No.:

Release Date: 2008-07-16 CA-EN-5 **Version Number:**

Attachment

Part of Kit **Product Code Container Size Kit Product Code**

CXT-6-DSP 205 L CXT-6-LSP12 1 L

Owner: Ford Motor Company Application: MATS

PRINTED DOCUMENT IS TRANSIENT

8 / 8 Page: