



Material Safety Data Sheet

FIR No.: 175204
Version Number: CA-EN-4

Level: 1
Release Date: 2008-07-16

1. Product and Company Identification

Product Name: SAE 5W-30 Synthetic Motor Oil
Product Code: See Attachment
Application: Motor oil
Supplier: Ford Motor Company of Canada
 Oakville, Ontario L6J 5E4
 1-800-392-3673

Emergency Telephone: Poison Control Center: 1-800-959-3673
 CHEMTREC: U.S. and Canada: 1-800-424-9300
 CHEMTREC: International: 1-703-527-3887

2. Composition/Information on Ingredients

This chemical product is a preparation.

Chemical Name	CAS Number	Percent Concentration	Hazard Classification
PETROLEUM DISTILLATES HYDROTREATED HEAVY PARAFFINIC	64742-54-7	60-100	HAZCOM RSMS_P_SOM

3. Hazards Identification

Health: Exposure to oil mist/fume/vapor may cause respiratory tract irritation. Inhalation of mist and vapors may irritate the nose, throat, and lungs. Ingestion may cause slight stomach irritation and discomfort. This product is not expected to cause eye irritation under normal conditions of use. Symptoms of slight eye irritation may result when direct contact occurs, or when exposed to high mist levels in poorly ventilated areas. No skin irritation can be expected from single short-term exposure to this product. Prolonged or repeated contact may produce some irritation.

Environment: Material contains a chemical which is a Hazardous Air Pollutant (HAP), regulated by the United States Clean Air Act.

4. First-Aid Measures

Inhalation: If gas/fume/vapor/dust/mist from the material is inhaled, remove the affected person immediately to fresh air. If irritation persists, get medical attention.

Skin Contact: Wash skin with soap and water. If irritation persists, get medical attention.

Eye Contact: In case of contact with eyes, rinse immediately with plenty of water for at least 15 minutes and seek medical attention. If irritation persists, get medical attention.

Material Safety Data Sheet

FIR No.: 175204
Version Number: CA-EN-4

Level: 1
Release Date: 2008-07-16

Ingestion: If the material is swallowed, get immediate medical attention or advice -- Do not induce vomiting.

5. Fire-Fighting Measures

Extinguishing Media: Dry chemical, foam, carbon dioxide.

Specific Methods: Use water to cool fire-exposed containers, structures, and to protect personnel.

Specific Hazards: Empty containers may retain product residue including Flammable or Explosive vapors. Do not cut, drill, grind, or weld near full, partially full, or empty product containers.
 Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.
 Upon decomposition, this product emits aldehydes.
 Irritating and toxic gases or fumes may be released during a fire.

Protection of Firefighters: Fire fighters should be equipped with NIOSH-approved, self-contained breathing apparatus (SCBA) and full protective clothing.

6. Accidental Release Measures

Personal Precautions: Eliminate all sources of ignition or flammables that may come into contact with a spill of this material.
 Surfaces may become slippery after spillage.
 Wear appropriate protective equipment and clothing during clean-up.

Environmental Precautions: Do not allow the spilled product to enter public drainage system or open water courses.

Methods for Cleaning Up: Contain the discharged material.
 Absorb the spilled material with an inert absorbent (nonflammable) material.
 Thoroughly wash the area after a spill or leak clean-up.

7. Handling and Storage

Handling:

Technical Measures: Avoid the generation of oil mists.

Precautions and Advice for Safe Handling: Elevated temperature or mechanical action may form vapors, mist, or fumes which may be irritating to the eyes, nose, throat, and lungs.
 Avoid breathing vapors or mist.
 Keep the container closed when not in use.

Storage: Technical Measures: No special precautions necessary.



Material Safety Data Sheet

FIR No.: 175204
Version Number: CA-EN-4

Level: 1
Release Date: 2008-07-16

Storage Conditions:

Do not store this material in open or unlabeled containers.
Keep the container tightly closed and in a cool, well-ventilated place.
Store this product away from strong oxidizing agents.

8. Exposure Controls/Personal Protection

Engineering Measures:

ENGINEERING CONTROL: Use adequate ventilation to control airborne concentrations below the exposure limits/guidelines. If user operations generate a vapor, dust, and/or mist, use process enclosure, local exhaust ventilation, or other engineering controls to control airborne levels below the recommended exposure limits/guidelines.

Control Parameters:

If oil mist is generated, observe the OSHA exposure limit of 5 mg/m3. Ford Motor Company recommends an exposure limit of 1.0 mg/m3.

Personal Protective Equipment:

Respiratory Protection:

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with the requirements of OSHA Respiratory Protection Standard 29 CFR 1910.134 and/or Canadian Standard CSA Z94.4.

Hand Protection:

The use of neoprene gloves is recommended.
The use of nitrile-latex gloves is recommended.

Eye Protection:

Wear safety glasses with side shields.

Skin and Body Protection:

Remove contaminated clothing and wash before reuse.

Hygiene Measures:

Wash thoroughly after handling.
When using this material, do not eat, drink or smoke.



Material Safety Data Sheet

FIR No.: 175204
Version Number: CA-EN-4

Level: 1
Release Date: 2008-07-16

9. Physical and Chemical Properties

Specific Gravity: 0.85 @15.6°C
Physical State: LIQUID
Form: OILY
Odor: MILD BLAND PETROLEUM
Color: DARK YELLOW
pH: N.AP
Temperature Range During which Changes in Physical State Occur:
Flash Point: 230 °C COC
Explosion Properties:
 UEL: N.AV
 LEL: N.AV
Solubility: INSOLUBLE IN WATER
Viscosity: 60@40°C cSt ASTM D93
Evaporation Rate: N.AV

10. Stability and Reactivity

Stability: This is a stable material.
Hazardous polymerization will not occur.
Conditions and Materials to Avoid: This product may react with strong oxidizing agents (bleach--sodium hypochlorite, calcium hypochlorite, hydrogen peroxide, permanganate, nitric acid, concentrated OXYGEN, perchlorates).
Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, and other low molecular weight hydrocarbons.

11. Toxicological Information

Chronic (Long Term) Toxicity: Base oil severely refined: Not carcinogenic in animal studies. Representative material passes IP-346, Modified Ames test, and/or other screening tests. Continuous long term contact with used motor oil has caused skin cancer in animal tests.

12. Ecological Information

No specific aquatic data available for this product.



Material Safety Data Sheet

FIR No.: 175204
Version Number: CA-EN-4

Level: 1
Release Date: 2008-07-16

13. Disposal Considerations

Waste from Residues: Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulation.

Contaminated Packaging: No consideration given when disposed of according to local, state, and Federal regulations.



Material Safety Data Sheet

FIR No.: 175204
Version Number: CA-EN-4

Level: 1
Release Date: 2008-07-16

14. Transport Information

U.S. Department of Transportation (DOT) 49 - CFR 172.101

This product is not regulated as a dangerous good.

Canadian Transportation of Dangerous Goods (T.D.G.) - TDGR Schedule II

This product is not regulated as a dangerous good.

Secretary of Communication and Transportation (SCT) - NOM-002-SCT2/1994 (Mexico)

This product is not regulated as a dangerous good.

International and Domestic Air Transportation - ICAO & IATA Section 4.2

This product is not regulated as a dangerous good.

International Water Transportation - IMDG Code Amendment 31-02

This product is not regulated as a dangerous good.

15. Regulatory Information

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Not a controlled product.

Don't pollute. Conserve resources. Return used oil to collection centers.

Material contains a chemical which is a Ford Motor Company Material of Concern. Use and release of this material should be minimized to the greatest extent possible.



16. Other Information

Key/Legend: N.AP = Not applicable; N.AV = Not available; ND = Not determined or No data; TLV = Threshold limit value; TWA = Time-weighted average; STEL = Short-term exposure limit; C = Ceiling limit

The following sections contain revisions OR 2
NEW statements. 3
15

Preparation Information:

The chemical identification and properties for this material were provided by the manufacturer. For Canadian locations, a manufacture's MSDS is available upon request. Health and safety information has been evaluated by the Occupational and Environmental Health Sciences Department, Ford Motor Company, Diagnostic Service Center II, 1800 Fairlane Drive, Allen Park, MI 48101, USA.





Material Safety Data Sheet

FIR No.: 175204
Version Number: CA-EN-4

Level: 1
Release Date: 2008-07-16

Disclaimer:

The information on this data sheet represents our current data and is accurate to the best of our knowledge as to the proper handling of this product under normal conditions and in accordance with the application specified on the packaging and/or technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.



Material Safety Data Sheet

FIR No.: 175204
Version Number: CA-EN-4

Level: 1
Release Date: 2008-07-16

Attachment

Product Code	Container Size	Part of Kit	Kit Product Code
CXO-5W30-LFS12	1 L		
