

ASHLAND

SAFETY DATA SHEET

Page: 1
Revision Date: 05/12/2008
Print Date: 9/9/2008
MSDS Number: R0340954
Version: 1.6

NAPA® MAC'S STARTING FLUID
NM7212

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Ashland	Regulatory Information Number	1-800-325-3751
P.O. Box 2219	Telephone	614-790-3333
Columbus, OH 43216	Emergency telephone	1-800-ASHLAND (1-800-274-5263)

Product name	NAPA® MAC'S STARTING FLUID
Product code	NM7212
Product Use Description	No data

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: aerosol

WARNING! EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPOR MAY CAUSE FLASH FIRE. CONTENTS UNDER PRESSURE. MAY AFFECT THE CENTRAL NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE IRRITATION. MAY CAUSE SKIN AND RESPIRATORY TRACT IRRITATION. PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE DERMATITIS AND BURNS.

Potential Health Effects

Routes of exposure

Inhalation, Skin absorption, Skin contact, Eye Contact

Eye contact

Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

Skin contact

Can cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, burns and other skin damage. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

Ingestion

ASHLAND

SAFETY DATA SHEET

Page: 2
Revision Date: 05/12/2008
Print Date: 9/9/2008
MSDS Number: R0340954
Version: 1.6

NAPA® MAC'S STARTING FLUID
NM7212

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

Inhalation

Breathing aerosol and/or mist is possible when material is sprayed. Aerosol and mist may present a greater risk of injury because more material may be present in the air than from vapor alone. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions), Individuals with preexisting heart disorders maybe more susceptible to arrhythmias (irregular heartbeats) if exposed to high concentrations of this material.

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), loss of appetite, loss of coordination, irregular heartbeat, narcosis (dazed or sluggish feeling)

Target Organs

Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: effects on hearing

Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA).

Reproductive hazard

There are no data available for assessing risk to the fetus from maternal exposure to this material.

ASHLAND

SAFETY DATA SHEET

NAPA® MAC'S STARTING FLUID
NM7212

Page: 3
Revision Date: 05/12/2008
Print Date: 9/9/2008
MSDS Number: R0340954
Version: 1.6

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Concentration
n-HEPTANE	142-82-5	>=70-<80%
ETHYL ETHER	60-29-7	>=15-<20%
CARBON DIOXIDE	124-38-9	>=1.5-<5%

4. FIRST AID MEASURES

Eyes

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

Skin

Remove contaminated clothing. Flush exposed area with large amounts of water. If skin is damaged, seek immediate medical attention. If skin is not damaged and symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to physician

Hazards: Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting.

Treatment: No information available.

ASHLAND
SAFETY DATA SHEET

NAPA® MAC'S STARTING FLUID
NM7212

Page: 4
Revision Date: 05/12/2008
Print Date: 9/9/2008
MSDS Number: R0340954
Version: 1.6

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Water mist, Carbon dioxide (CO2), Dry chemical

Hazardous combustion products

carbon dioxide and carbon monoxide, various hydrocarbons

Precautions for fire-fighting

Material is volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations near the material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

Methods for cleaning up

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Avoid prolonged or frequently repeated skin contact with this material. Skin contact can be minimized by wearing impervious protective gloves. As with all products of this nature, good personal hygiene is essential. Hands and other exposed areas should be washed thoroughly with soap and water after contact, especially before eating and/or smoking. Regular laundering of contaminated

ASHLAND

SAFETY DATA SHEET

Page: 5
Revision Date: 05/12/2008
Print Date: 9/9/2008
MSDS Number: R0340954
Version: 1.6

NAPA® MAC'S STARTING FLUID
NM7212

clothing is essential to reduce indirect skin contact with this material. Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.

Storage

Do not store near extreme heat, open flame, or sources of ignition.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

n-HEPTANE		142-82-5
ACGIH	time weighted average	400 ppm
ACGIH	Short term exposure limit	500 ppm
NIOSH	Recommended exposure limit	85 ppm
	(REL):	
NIOSH	Recommended exposure limit	350 mg/m3
	(REL):	
NIOSH	Ceiling Limit Value and	440 ppm
	Time Period (if specified):	
NIOSH	Ceiling Limit Value and	1,800
	Time Period (if specified):	mg/m3
OSHA Z1	Permissible exposure limit	500 ppm
OSHA Z1	Permissible exposure limit	2,000
		mg/m3
OSHA Z1A	time weighted average	400 ppm
OSHA Z1A	time weighted average	1,600
		mg/m3
OSHA Z1A	Short term exposure limit	500 ppm
OSHA Z1A	Short term exposure limit	2,000
		mg/m3
US CA OEL	Time Weighted Average	400 ppm
	(TWA) Permissible Exposure	
	Limit (PEL):	
US CA OEL	Time Weighted Average	1,600
	(TWA) Permissible Exposure	mg/m3
	Limit (PEL):	
US CA OEL	Short term exposure limit	500 ppm
US CA OEL	Short term exposure limit	2,000
		mg/m3
ACGIH	time weighted average	400 ppm
ACGIH	Short term exposure limit	500 ppm

ASHLAND

SAFETY DATA SHEET

NAPA® MAC'S STARTING FLUID
NM7212

Page: 6
Revision Date: 05/12/2008
Print Date: 9/9/2008
MSDS Number: R0340954
Version: 1.6

ETHYL ETHER		60-29-7
ACGIH	time weighted average	400 ppm
ACGIH	Short term exposure limit	500 ppm
OSHA Z1	Permissible exposure limit	400 ppm
OSHA Z1	Permissible exposure limit	1,200 mg/m3
CARBON DIOXIDE		124-38-9
ACGIH	time weighted average	5,000 ppm
ACGIH	Short term exposure limit	30,000 ppm
NIOSH	Recommended exposure limit (REL):	5,000 ppm
NIOSH	Recommended exposure limit (REL):	9,000 mg/m3
NIOSH	Short term exposure limit	30,000 ppm
NIOSH	Short term exposure limit	54,000 mg/m3
OSHA Z1	Permissible exposure limit	5,000 ppm
OSHA Z1	Permissible exposure limit	9,000 mg/m3

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Eye protection

Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection

Wear resistant gloves (consult your safety equipment supplier).
Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local

ASHLAND

SAFETY DATA SHEET

Page: 7
Revision Date: 05/12/2008
Print Date: 9/9/2008
MSDS Number: R0340954
Version: 1.6

NAPA® MAC'S STARTING FLUID
NM7212

safety equipment supplier to determine the proper personal protective equipment for your use.

Respiratory protection

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	aerosol
Form	aerosol
Colour	No data
Odour	No data
Boiling point/boiling range	34.60 °C / 94.3 °F @ 1,013.23 hPa
pH	No data
Flash point	No data
Evaporation rate	No data
Explosion limits	1.05 %(V) 36.5 %(V)
Vapour pressure	717.26 hPa @ 77 °F / 25 °C
Vapour density	No data
Density	0.7114 g/cm3 @ 60.01 °F / 15.56 °C
Solubility	No data
Partition coefficient: n-octanol/water	No data
log Pow	no data available
Autoignition temperature	No data

10. STABILITY AND REACTIVITY

Stability
Stable.

Conditions to avoid

ASHLAND

SAFETY DATA SHEET

Page: 8
Revision Date: 05/12/2008
Print Date: 9/9/2008
MSDS Number: R0340954
Version: 1.6

NAPA® MAC'S STARTING FLUID
NM7212

Avoid heat, open flame, and prolonged storage at elevated temperatures.

Incompatible products

strong oxidizing agents

Hazardous decomposition products

carbon dioxide and carbon monoxide, various hydrocarbons

Hazardous reactions

Product will not undergo hazardous polymerization.

Thermal decomposition

No data

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity

n-HEPTANE	LD 50 Rat: > 15,000 mg/kg
ETHYL ETHER	LD 50 Rat: 3,230 - 3,920 mg/kg
CARBON DIOXIDE	no data available

Acute inhalation toxicity

n-HEPTANE	LC 50 Rat: 103 g/m ³ , 4 h
ETHYL ETHER	LC 50 Rat: 32000 ppm, 4 h
CARBON DIOXIDE	no data available

Acute dermal toxicity

n-HEPTANE	LD 50 Rabbit: > 2,001 mg/kg
ETHYL ETHER	no data available
CARBON DIOXIDE	no data available

12. ECOLOGICAL INFORMATION

Aquatic toxicity

Acute and Prolonged Toxicity to Fish

No data

ASHLAND

SAFETY DATA SHEET

Page: 9
Revision Date: 05/12/2008
Print Date: 9/9/2008
MSDS Number: R0340954
Version: 1.6

NAPA® MAC'S STARTING FLUID
NM7212

Acute Toxicity to Aquatic Invertebrates
No data

Environmental fate and pathways
No data

13. DISPOSAL CONSIDERATIONS

Waste disposal methods

Dispose of in accordance with all applicable local, state and federal regulations. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION

IMDG:

UN1950, AEROSOLS 2.1,

IATA_P:

UN1950, Aerosols, flammable 2.1,

IATA_C:

UN1950, Aerosols, flammable 2.1,

CFR_ROAD:

UN1950, Aerosols 2.1,

CFR_RAIL:

UN1950, Aerosols 2.1,

CFR_INWTR:

UN1950, Aerosols 2.1,

Dangerous goods descriptions (if indicated above) may not reflect package size, quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

15. REGULATORY INFORMATION

California Prop. 65

WARNING! This product contains a chemical known in the State of California to cause cancer.

ASHLAND

SAFETY DATA SHEET

Page: 10
Revision Date: 05/12/2008
Print Date: 9/9/2008
MSDS Number: R0340954
Version: 1.6

NAPA® MAC'S STARTING FLUID
NM7212

BENZENE

WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

BENZENE

TOLUENE

SARA Hazard Classification Acute Health Hazard

SARA 313 Component(s)

Reportable quantity - Product

US. EPA CERCLA Hazardous Substances (40 CFR 302) 511 lbs

Reportable quantity - Components

n-HEPTANE	142-82-5	none
ETHYL ETHER	60-29-7	100 lbs
CARBON DIOXIDE	124-38-9	none

	Health	Flammability	Reactivity	Other
HMIS	1	4	0	
NFPA	1	4	0	

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).