

SAFETY DATA SHEET

1. Identification

Product identifier	Hydraulic & Jack Oil
Other means of identification	
Product code	SL2552, SL2553, SL2555, SL2621
Recommended use	Hydraulic and jack oil
Recommended restrictions	None known.
Manufacturer/Importer/Supplie	r/Distributor information
Manufactured or sold by:	
Company name	CRC Industries, Inc.
Address	885 Louis Dr.
	Warminster, PA 18974 US
Telephone	
General Information	215-674-4300
Technical	800-521-3168
Assistance	
Customer Service	800-272-4620
24-Hour Emergency	800-424-9300 (US)
(CHEMTREC)	703-527-3887 (International)
Website	www.crcindustries.com
2. Hazard(s) identificatio	n
Physical hazards	Not classified.
Health hazards	Not classified.

Health hazards	Not classified.
Environmental hazards	Not classified.
OSHA defined hazards	Not classified.
Label elements	
Hazard symbol	None.
Signal word	None.
Hazard statement	The mixture does not meet the criteria for classification.
Precautionary statement	
Prevention	Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use. Observe good industrial hygiene practices.
Response	Wash hands after handling.
Storage	Store away from incompatible materials.
Disposal	Dispose of waste and residues in accordance with local authority requirements.
Hazard(s) not otherwise classified (HNOC)	None known.

3. Composition/information on ingredients

Mixtures			
Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), hydrotreated heavy paraffinic		64742-54-7	60 - 70
Distillates (petroleum), solvent-refined heavy naphthenic		64741-96-4	30 - 40

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
Skin contact	Wash off with plenty of water. Remove and isolate contaminated clothing and shoes. Get medical attention if irritation develops and persists. Wash contaminated clothing before reuse.
Eye contact	Rinse immediately with plenty of water, also under the eyelids. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Drink 1 or 2 glasses of water. Do not induce vomiting without advice from poison control center. Never give anything by mouth to a victim who is unconscious or is having convulsions. Get medical attention if symptoms occur. If ingestion of a large amount does occur, call a poison control center immediately.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Cool containers exposed to heat with water spray and remove container, if no risk is involved.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. For personal protection, see section 8 of the SDS.	
Methods and materials for	The product is immiscible with water and will spread on the water surface.	
containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.	
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.	
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Prevent entry into waterways, sewer, basements or confined areas.	
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.	
7. Handling and storage		
Precautions for safe handling	Wear appropriate personal protective equipment. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. When using, do not eat, drink or smoke. Wash contaminated clothing before reuse. Use appropriate container to avoid environmental contamination. For product usage instructions, please see the product label.	
Conditions for safe storage, including any incompatibilities	Keep away from heat and sources of ignition. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Keep container tightly closed. Store away from incompatible materials (see Section 10 of the SDS).	

cupational exposure limits			
U.S OSHA	Tumo	Value	
Components	Туре	Value	
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	
	Air Contaminants (29 CFR 1910.	1000)	
Components	Туре	Value	Form
Distillates (petroleum), solvent-refined heavy naphthenic (CAS 64741-96-4)	PEL	5 mg/m3	Mist.
		2000 mg/m3 500 ppm	
ACGIH			
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. ACGIH Threshold Limit Va	TWA	5 mg/m3	Inhalable fraction
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.
Distillates (petroleum), solvent-refined heavy naphthenic (CAS 64741-96-4)	TWA	5 mg/m3	Inhalable fraction.
U.S NIOSH			
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	STEL	10 mg/m3	Mist
	TWA	5 mg/m3	Mist
US. NIOSH: Pocket Guide to C	hemical Hazards		_
Components	Туре	Value	Form
Distillates (petroleum), solvent-refined heavy naphthenic (CAS 64741-96-4)	Ceiling	1800 mg/m3	
,	STEL	10 mg/m3	Mist.
logical limit values	No biological exposure limits noted f	or the ingredient(s).	
ntrols c	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. General ventilation normally adequate.		
-	ich as personal protective equip n Near safety glasses with side shield		
Skin protection Hand protection	Vear protective gloves such as: Nitr	ile. Polyvinyl chloride (PVC).	
Other	Near suitable protective clothing.		
Respiratory protection	If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.		
ľ	preathing apparatus in confined spa	ces and for emergencies. Air m	

General hygiene considerations

9. Physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Liquid.
Color	Amber. Red.
Odor	Mild petroleum.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	680 °F (360 °C) estimated
Flash point	380 °F (193.3 °C) Pensky-Martens Closed Cup
Evaporation rate	Slow.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Vapor pressure	0.003 hPa estimated
Vapor density	> 5 (air = 1)
Relative density	0.87 - 0.89
Solubility (water)	Insoluble.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	500 °F (260 °C) estimated
Decomposition temperature	Not available.
Viscosity (kinematic)	49.8 - 58 mm²/s (104 °F (40 °C))
Percent volatile	98.9 % estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Heat, flames and sparks. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Carbon oxides.

11. Toxicological information

Information on likely routes of	exposure		
Inhalation	Prolonged or excessive inhalation may cause respiratory tract irritation.		
Skin contact	Prolonged skin contact may cause temporary irritation. Repeated exposure may cause skin dryness or cracking.		
Eye contact	Direct contact with eyes may cause temporary irritation.		
Ingestion	Expected to be a low ingestion hazard.		
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.		
Information on toxicological of	facto		

Information on toxicological effects

Acute toxicity	Not available.		
Product	Species	Test Results	
Hydraulic & Jack Oil			
Acute			
Dermal			
LD50	Rabbit	5034 mg/kg estimated	
Oral			
LD50	Rat	8806 mg/kg estimated	
* Estimates for product may b	e based on additional component	data not shown.	
Skin corrosion/irritation	Prolonged skin contact may cau		
Serious eye damage/eye irritation	Direct contact with eyes may ca	use temporary irritation.	
Respiratory sensitization	Not a respiratory sensitizer.		
Skin sensitization	This product is not expected to o	cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate pro mutagenic or genotoxic.	oduct or any components present at greater than 0.1% are	
Carcinogenicity	This product is not considered to	be a carcinogen by IARC, ACGIH, NTP, or OSHA.	
IARC Monographs. Overall	Evaluation of Carcinogenicity		
Not available. US. National Toxicology Pro Not available.	ogram (NTP) Report on Carcinog	gens	
Reproductive toxicity	This product is not expected to a	cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.		
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	Not classified.		
Chronic effects	Prolonged inhalation may be harmful.		
Further information	This product has no known adve	erse effect on human health.	
12. Ecological information	n		
Ecotoxicity	The product is not classified as	environmentally hazardous. However, this does not exclude the spills can have a harmful or damaging effect on the environment.	
Product	Species	Test Results	
Hydraulic & Jack Oil			
Aquatic			
Acute			
Fish	LC50 Fish	946.2366 mg/l, 96 hours estimated	
* Estimates for product may b	e based on additional component	data not shown.	
Persistence and degradability	No data is available on the degr		
Bioaccumulative potential			
Mobility in soil	No data available.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		
13. Disposal consideratio	ns		
Disposal of waste from residues / unused products	This product is not a RCRA haza containers may be recycled. Col	ardous waste (See 40 CFR Part 261.20 – 261.33). Empty llect and reclaim or dispose in sealed containers at licensed waste ance with all applicable regulations.	
Hazardous waste code	Not regulated.		
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.		
Material name: Hydraulic & Jack Oil		SDS U	

DOT

Not regulated as dangerous goods.

ΙΑΤΑ

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

15. Regulatory information

US federal regulations

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)	Not regulated.
Food and Drug	Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312	Immediate Hazard - No
Hazard categories	Delayed Hazard - No
-	Fire Hazard - No
	Pressure Hazard - No
	Reactivity Hazard - No
SARA 302 Extremely	No

hazardous substance

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)

Distillates (petroleum), solvent-refined heavy naphthenic (CAS 64741-96-4)

- US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100) Not listed.
- US. Massachusetts RTK Substance List
 - Distillates (petroleum), solvent-refined heavy naphthenic (CAS 64741-96-4)
- US. New Jersey Worker and Community Right-to-Know Act
 - Not listed.

US. Rhode Island RTK

None.

US. Pennsylvania Worker and Community Right-to-Know Law Not listed.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR 51.100(s))	Not determined
Consumer products (40 CFR 59, Subpt. C)	Not regulated

State

Consumer products	Not regulated
VOC content (CA)	0 %
VOC content (OTC)	0 %

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	10-16-2015
Prepared by	Allison Cho
Version #	01
Further information	Not available.
HMIS® ratings	Health: 1 Flammability: 1 Physical hazard: 0 Personal protection: B
NFPA ratings	Health: 1 Flammability: 1 Instability: 0
NFPA ratings	
Disclaimer	The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further

professional, or CRC Industries.

clarification of any information contained on this (M)SDS consult your supervisor, a health & safety