MFG'S INFORMATION				HAZARD RATING		
Castle Products, Inc. 424 St. Paul Street		0-least, 1-slight, 2-moderate, 3-high			Health Fire	2
Rochester, NY 14605		4-extreme, A-goggles, B-goggles & gloves, C-goggles & gloves &			Reactivity	1
1-800-876-0222	protective wear				Personal	B
EMERGENCY (585) 275-323		wear			1 crsonar	Б
	the second se	TION I DESCRIP	TION			
STOCK NUMBER TRADE NAME & SYNONYMS						
		Castle Whit	te Wall Tire (Bulk)			
CHEMICAL FAMILY		FORMULA	1	A MARKED	and the second	ALL DESCRIPTION OF
	SECTION II	HAZARDOUS IN	NGREDIENTS	- 10		
	CAS NO.	PEL	TLV	STEL	(%)	
Monobutyl Ether	112-34-5		50PPM (skin)		<10	
Alkyl Benzene Sulfonic Acid	27176-87-0				<10	
Sodium Hydroxide	1310-73-2		ACGIH 2 mg/m	13	<10	
	SECTI	ON III PHYSICAI	L DATA		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	198
BOILING POINT:	230°F	SPECIFIC	GRAVITY (H ₂ O=1)		.990	
VAPOR PRESSURE:	.2	PERCENT	VOLATILE BY VOL	%	.018	
VAPOR DENSITY (air=1)	1.1	EVAPORA	TION RATE (Butyl A	cetate=1		
SOLUBILITY IN WATER:	complete	APPEARA	NCE & ODOR		purple/lemon	
Contraction of the second s	SECTION IV FIRI	E AND EXPLOSIC	N HAZARD DATA			
FLASH POINT(method used)		BLE LIMITS	LEL		UEL	
200° TCC ASTM56	5					
EXTINGUISHING MEDIA: C		е.				
SPECIAL FIRE FIGHTING PR	OCEDURES: Alcohol	type foam, water s	pray can react with an	photeric	metals (such as	
aluminum) generating hydrogen	which is flammable or	explosive.				
UNUSUAL FIRE & EXPLOSIC	ON HAZARDS:	i i i i i i i i i i i i i i i i i i i				
		V HEALTH HAZ	ARD DATA	10.50	and the second second	100
THRESHOLD LIMIT VALUE:	50PPM(skin) ACGIH/	CRF29/1000table-0	Oral-mus/LD50:1407n	ngkg		
FFFFCT OF OVEREXPOSURI	E: Eve and skin irritation	on. Ingestion-nause	ea.			
EMERGENCY & FIRST AID P	ROCEDURES: Avoid	prolonged contact	with skin. Flush with v	water, DC	NOT INGEST	. A
natural emetic if ingested give p	lenty of water, contact	ohysician.			A PARAL C	
Internet entrette in ingeneration of		VVI REACTIVI	ΓΥ DATA			
STABILITY:	STABLE XXXXX		ISTABLE			
INCOMPATIBILITY (mat'l to a						
HAZARDOUS DECOMPOSIT	ION PRODUCTS: The	ermal decompositio	n or burning may caus	e carbon	monoxide and/c	or carbon
dioxide.						
HAZARDOUS POLYMERIZA	TION: MAY OCO	CUR	WON'T OCCU	R XXXX	XXXXXXXX	
		SPILL OR LEAK	PROCEDURES	Land		
STEPS TO BE TAKEN IN CAS	SE MATERIAL IS REI	EASED OR SPILL	LED: Recover al usab	le materia	al.	
WASTE DISPOSAL METHOD	Flush with large quar	ntities of water in a	ccordance with local, s	state and	federal regulation	ns.
Biodegradable.	. Trush with harbe qua					
Diodegradable.	SECTION VIII SPI	ECIAL PROTECTI	ON INFORMATION			
RESPIRATORY PROTECTION	Ves in confined area	IS.				
		IECHANICAL	OTHE	R		
PROTECTIVE GLOVES: Yes		Derningerig				
EYE PROTECTION: Yes						
OTHER PROTECTIVE EQUIP	MENT					
UTHER FROTECTIVE EQUI	SECTION	IX SPECIAL PRE	CAUTIONS			
PRECAUTIONS TO BE TAKE	N IN HANDI ING AN	D STORING: Stor	re above freezing. Stor	e away fi	om acids. Store	away
from aluminum, in case of leak.		D STORATO, Stor				100.25
from arumnum, in case of leak.						
PRODUCT #: 72	DATE PR	EPARED: 08/14/8	86	DATE	REVISED: 12/0	07/02