

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date 10.08.2015

Revision: 10.08.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Slime Pro Tire Sealant OTR (Over The Road)**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Sealant
- **1.3 Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
(North America)
ITW Global Tire Repair, Inc.
125 Venture Drive, Suite 210, San Luis Obispo, CA 93401
Tel (805) 489-0490

- (Europe)
ITW Global Tire Repair, Europe GmbH
Carl-Benz Str. 10, 88696 Owingen, Germany
Tel 0049 7551-9200-100

- Only representative of a non-Community manufacturer
H2 Compliance
Rubicon Building, CIT Campus, Bishopstown, Cork, Ireland
Tel +353 21 486 8122
E-Mail info@h2compliance.com
- **1.4 Emergency telephone number:**
ChemTel Inc.
(800)255-3924, +1 (813)248-0585



SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
The product is not classified as hazardous according to the Globally Harmonized System (GHS).
The product is not classified as hazardous according to the CLP regulation.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008** Not Regulated
- **Hazard pictograms** Not Regulated
- **Signal word** Not Regulated

- **Hazard-determining components of labelling:** None.
- **Hazard statements** Not Regulated
- **NFPA ratings (scale 0 - 4)**



(Cont'd. on page 2)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date 10.08.2015

Revision: 10.08.2015

Trade name: Slime Pro Tire Sealant OTR (Over The Road)

(Cont'd. from page 1)

- **HMIS-ratings (scale 0 - 4)**

HEALTH	0	Health = *0
FIRE	1	Fire = 1
REACTIVITY	0	Reactivity = 0

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.
- **Dangerous components:**
None in reportable quantities.

CAS: 56-81-5 EINECS: 200-289-5	glycerol	substance with a Community workplace exposure limit	25-50%
CAS: 9004-34-6 EINECS: 232-674-9	Cellulose	substance with a Community workplace exposure limit	≤ 2,5%

- **Additional information:** For the wording of the listed Hazard Statements refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** No special measures required.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact:**
Remove contact lenses if worn.
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**
Rinse out mouth and then drink plenty of water.
Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**
Gastric or intestinal disorders.
Coughing
Nausea
Slight irritant effect on eyes.
- **Hazards** No further relevant information available.

(Cont'd. on page 3)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date 10.08.2015

Revision: 10.08.2015

Trade name: Slime Pro Tire Sealant OTR (Over The Road)

(Cont'd. from page 2)

- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** None.
- **5.2 Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.
- **Additional information** Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Use respiratory protective device against the effects of fumes/dust/aerosol.
Ensure adequate ventilation
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Allow to solidify. Pick up mechanically.
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
Clean the affected area carefully; suitable cleaners are:
Warm water and cleansing agent
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Store in cool, dry place in tightly closed receptacles.
Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
When heated the product forms flammable fumes.

(Cont'd. on page 4)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date 10.08.2015

Revision: 10.08.2015

Trade name: Slime Pro Tire Sealant OTR (Over The Road)

(Cont'd. from page 3)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Avoid storage near extreme heat, ignition sources or open flame.
- **Information about storage in one common storage facility:**
Store away from foodstuffs.
Do not store together with oxidising and acidic materials.
- **Further information about storage conditions:** Protect from frost.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see section 7.
- **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

56-81-5 glycerol

PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
TLV (USA)	TLV withdrawn-insufficient data human occup. exp.
EL (Canada)	Long-term value: 10* 3** mg/m ³ *mist; **mist, respirable
EV (Canada)	Long-term value: 10 mg/m ³

9004-34-6 Cellulose

PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV (USA)	Long-term value: 10 mg/m ³
EL (Canada)	Long-term value: 10 mg/m ³
EV (Canada)	Long-term value: 10 mg/m ³ paper fibre, total dust

- **DNELs** No further relevant information available.
- **PNECs** No further relevant information available.
- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
The usual precautionary measures are to be adhered to when handling chemicals.
No further relevant information available.
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes.

(Cont'd. on page 5)

Safety Data Sheet


according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date 10.08.2015

Revision: 10.08.2015

Trade name: Slime Pro Tire Sealant OTR (Over The Road)

(Cont'd. from page 4)

- **Respiratory protection:**
Not required under normal conditions of use.
For spills, respiratory protection may be advisable.
- **Protection of hands:**
Not required under normal conditions of use.
Wear protective gloves to handle contents of damaged or leaking units.
- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
Nitrile rubber, NBR
Neoprene gloves
- **Eye protection:**
 Safety glasses
- **Body protection:**
Not required under normal conditions of use.
Protection may be required for spills.
- **Limitation and supervision of exposure into the environment** No special requirements.
- **Risk management measures** No special requirements.

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

Form:	Pasty
Colour:	Different according to colouring
Odour:	Light
Odour threshold:	Not determined.
- **pH-value at 20 °C (68 °F):** 9,5 ± 0,5
- **Change in condition**

Melting point/Melting range:	<-30 °F / <-34 °C (<-22 °F / <-29 °F)
Boiling point/Boiling range:	>212 °F / >100 °C (>414 °F / >212 °F)
- **Flash point:** >200 °F / >93 °C (>392 °F / >199 °F)
- **Flammability (solid, gaseous):** Not applicable.
- **Auto/Self-ignition temperature:** Not determined.
- **Decomposition temperature:** Not determined.
- **Self-igniting:** Product is not self-igniting.
- **Danger of explosion:** Product does not present an explosion hazard.
- **Explosion limits:**

Lower:	Not determined.
--------	-----------------

(Cont'd. on page 6)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date 10.08.2015

Revision: 10.08.2015

Trade name: Slime Pro Tire Sealant OTR (Over The Road)

(Cont'd. from page 5)

- **Upper:** Not determined.
- **Vapour pressure:** Not determined.
- **Density at 20 °C (68 °F):** 0,9 ± 0,1 g/cm³ (7,511 ± 0,835 lbs/gal)
- **Relative density** Not determined.
- **Vapour density** Not determined.
- **Evaporation rate** Not determined.
- **Solubility in / Miscibility with water:** Partly miscible.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - Dynamic at 20 °C (68 °F):** >500000 cPs
 - Kinematic:** Not determined.
- **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions**
Reacts with strong acids.
Reacts with strong oxidising agents.
- **10.4 Conditions to avoid** Store away from oxidising agents.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
Possible in traces.
Carbon monoxide and carbon dioxide
Nitrogen oxides (NOx)
Sulphur oxides (SOx)

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**
- **LD/LC50 values relevant for classification:** None.
- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Slight irritant effect on eyes.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):**
- **Germ cell mutagenicity**
Based on available data, the classification criteria are not met.
- **Carcinogenicity**
Based on available data, the classification criteria are not met.
- **Reproductive toxicity**
Based on available data, the classification criteria are not met.

(Cont'd. on page 7)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date 10.08.2015

Revision: 10.08.2015

Trade name: Slime Pro Tire Sealant OTR (Over The Road)

(Cont'd. from page 6)

- **STOT-single exposure**
Based on available data, the classification criteria are not met.
- **STOT-repeated exposure**
Based on available data, the classification criteria are not met.
- **Aspiration hazard**
Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** The product is biodegradable after prolonged adaptation.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Due to mechanical actions of the product (e.g. agglutinations) damages may occur.
- **Additional ecological information:**
- **General notes:**
Avoid transfer into the environment.
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Smaller quantities can be disposed of with household waste.
Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.
Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to local official regulations.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

SECTION 14: Transport information

- **14.1 UN-Number**
- **DOT, ADR, IMDG, IATA** Not Regulated
- **14.2 UN proper shipping name**
- **DOT, ADR, IMDG, IATA** Not Regulated

(Cont'd. on page 8)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date 10.08.2015

Revision: 10.08.2015

Trade name: Slime Pro Tire Sealant OTR (Over The Road)

(Cont'd. from page 7)

- **14.3 Transport hazard class(es)**
- DOT, ADR, ADN, IMDG, IATA
- **Class** Not Regulated
- **14.4 Packing group**
- DOT, ADR, IMDG, IATA Not Regulated
- **14.5 Environmental hazards:**
- **Marine pollutant:** No
- **14.6 Special precautions for user** Not applicable.
- **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable.
- **UN "Model Regulation":** Not Regulated

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· Section 355 (extremely hazardous substances):
--

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):
--

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65 (California):

· Chemicals known to cause cancer:

Reference to talc is based on unbound respirable particles and is not generally applicable to product as supplied.
--

14807-96-6 Talc (Mg ₃ H ₂ (SiO ₃) ₄)
--

· Chemicals known to cause reproductive toxicity for females:
--

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:
--

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· Carcinogenic Categories

· EPA (Environmental Protection Agency)
--

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer)

14807-96-6 Talc (Mg ₃ H ₂ (SiO ₃) ₄)
--

2B

· TLV (Threshold Limit Value established by ACGIH)

14807-96-6 Talc (Mg ₃ H ₂ (SiO ₃) ₄)
--

A4

(Cont'd. on page 9)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date 10.08.2015

Revision: 10.08.2015

Trade name: Slime Pro Tire Sealant OTR (Over The Road)

(Cont'd. from page 8)

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients are listed.

· **Canada**

· **Canadian Domestic Substances List (DSL)**

All ingredients are listed.

· **Canadian Ingredient Disclosure list (limit 0.1%)**

None of the ingredients are listed.

· **Canadian Ingredient Disclosure list (limit 1%)**

None of the ingredients are listed.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I**

None of the ingredients are listed.

· **Other regulations, limitations and prohibitive regulations**

· **Substances of very high concern (SVHC) according to REACH, Article 57**

None of the ingredients are listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMS: Hazardous Materials Identification System (USA)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

· **Sources**

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

(Cont'd. on page 10)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date 10.08.2015

Revision: 10.08.2015

Trade name: Slime Pro Tire Sealant OTR (Over The Road)

Website: www.chemtelinc.com

(Cont'd. from page 9)