

**Diesel No. 2 Test Fuel**

Version 1.12

Revision Date 2016-05-10

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****Product information**

Product Name : Diesel No. 2 Test Fuel  
Material : 1117144, 1114932, 1114380, 1114379, 1111796, 1111792,  
1111793, 1111721, 1108397, 1097307, 1096433, 1083233,  
1096612, 1084817, 1097324, 1097322, 1097310, 1089768,  
1079939, 1097309, 1090864, 1077073, 1077061, 1090863,  
1069145, 1100027, 1099634, 1090866, 1099603, 1090314,  
1097785, 1087561, 1092489, 1076410, 1102501, 1097387,  
1090432, 1090433, 1100452, 1097386, 1078955, 1100842,  
1077075, 1097308, 1100531, 1069147, 1090862, 1078060,  
1077077, 1068920, 1078988, 1017963, 1017962, 1036152,  
1024299, 1024300, 1017964, 1024301, 1017977, 1024303,  
1017981, 1017980, 1017965, 1017978, 1017967, 1017966,  
1017979, 1024297, 1024293, 1029744, 1024292, 1017982,  
1024294, 1024296, 1024302, 1024304, 1024309, 1024308,  
1024307, 1024306, 1024295, 1024305, 1024298, 1029490,  
1104964, 1104939, 1104952, 1104938, 1104941, 1104963,  
1104956, 1104955, 1104953

**Company** : Chevron Phillips Chemical Company LP  
Specialty Chemicals  
10001 Six Pines Drive  
The Woodlands, TX 77380

**Emergency telephone:****Health:**

866.442.9628 (North America)

1.832.813.4984 (International)

**Transport:**

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: +800 CHEMCALL (+800 2436 2255) China:+86-21-22157316

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Responsible Department : Product Safety and Toxicology Group  
E-mail address : SDS@CPChem.com  
Website : www.CPChem.com

**SECTION 2: Hazards identification****Classification of the substance or mixture**

**Diesel No. 2 Test Fuel**

Version 1.12

Revision Date 2016-05-10

This product has been classified in accordance with the hazard communication standard 29 CFR 1910.1200; the SDS and labels contain all the information as required by the standard.

**Emergency Overview****Danger**

**Form:** Liquid    **Physical state:** Liquid    **Color:** Pale yellow to brown (if undyed), red to purple (dyed)    **Odor:** Mild

OSHA Hazards : Flammable Liquid, Harmful by inhalation., Moderate skin irritant, Carcinogen, Target Organ Effects, Aspiration hazard

**Classification**

: Flammable liquids , Category 3  
 Acute toxicity , Category 4 , Inhalation  
 Skin irritation , Category 2  
 Carcinogenicity , Category 2  
 Specific target organ systemic toxicity - repeated exposure , Category 1 , Eyes, Blood  
 Specific target organ systemic toxicity - repeated exposure , Category 2 , Liver  
 Aspiration hazard , Category 1

**Labeling**

Symbol(s)



Signal Word

: Danger

Hazard Statements

: H226: Flammable liquid and vapor.  
 H304: May be fatal if swallowed and enters airways.  
 H315: Causes skin irritation.  
 H332: Harmful if inhaled.  
 H351: Suspected of causing cancer.  
 H372: Causes damage to organs (Eyes, Blood, Liver) through prolonged or repeated exposure.

Precautionary Statements

: **Prevention:**  
 P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
 P233 Keep container tightly closed.  
 P240 Ground/bond container and receiving equipment.  
 P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
 P242 Use only non-sparking tools.  
 P243 Take precautionary measures against static discharge.  
 P260 Do not breathe dust/fume/gas/mist/vapor/spray.  
 P264 Wash skin thoroughly after handling.  
 P270 Do not eat, drink or smoke when using this product.  
 P271 Use only outdoors or in a well-ventilated area.  
 P280 Wear protective gloves/ eye protection/ face protection.

**Diesel No. 2 Test Fuel**

Version 1.12

Revision Date 2016-05-10

P281 Use personal protective equipment as required.

**Response:**

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

**Storage:**

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Carcinogenicity:****IARC**

Group 2B: Possibly carcinogenic to humans

Naphthalene 91-20-3

**NTP**

Reasonably anticipated to be a human carcinogen

Naphthalene 91-20-3

**ACGIH**

Confirmed animal carcinogen with unknown relevance to humans

Diesel fuel 68476-34-6

**SECTION 3: Composition/information on ingredients**

Synonyms : Diesel 0.05 LS Emiss Cert Test Fuel- Cummins  
 Diesel CEC (RF-73-T-90)  
 Diesel Reference Fuels, Diesel Cert Fuel, Oil Classification  
 Diesel  
 Diesel 2007 Emission Certification Fuel  
 Diesel Euro-II Cert Fuel  
 Diesel Euro-IV Cert Fuel  
 Diesel 0.05 LS Emiss Cert Test Fuel- ITE  
 PC-10 Diesel Test Fuel  
 Locomotive Diesel Certification Fuel  
 Diesel Euro-III Cert Fuel  
 Diesel Special Test Fuel  
 Diesel CEC (RF-03-A-84)  
 Ultra High Cetane Check Fuel (ASTM) Diesel  
 Diesel 2004 Tier 2 Fuel  
 0.05% Sulfur Diesel Fuel - JASO  
 No Sulfur (less than 3 PPM) Diesel Test Fuel  
 Diesel Caterpillar F173  
 Diesel Caterpillar 1E2973

**Diesel No. 2 Test Fuel**

Version 1.12

Revision Date 2016-05-10

Caterpillar China Certification Diesel Fuel Stage III

Molecular formula : UVCB

Component	CAS-No.	Weight %
Diesel fuel	68476-34-6	100
Naphthalene	91-20-3	0 - 1

**SECTION 4: First aid measures**

- General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Do not leave the victim unattended.
- If inhaled : Keep respiratory tract clear. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Take victim immediately to hospital.

**SECTION 5: Firefighting measures**

- Flash point : 47 °C (117 °F) minimum
- Autoignition temperature : No data available
- Suitable extinguishing media : Dry chemical. Carbon dioxide (CO<sub>2</sub>). Alcohol-resistant foam.
- Unsuitable extinguishing media : High volume water jet.
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed

**Diesel No. 2 Test Fuel**

Version 1.12

Revision Date 2016-05-10

- containers.
- Fire and explosion protection : Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open flames, hot surfaces and sources of ignition.
- Hazardous decomposition products : Hydrocarbons. Carbon oxides.

**SECTION 6: Accidental release measures**

- Personal precautions : Use personal protective equipment. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**SECTION 7: Handling and storage****Handling**

- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Only add small quantities of acids and bases to water, never the opposite. Always use stirring. Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open flames, hot surfaces and sources of ignition.

**Storage**

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

**Diesel No. 2 Test Fuel**

Version 1.12

Revision Date 2016-05-10

**SECTION 8: Exposure controls/personal protection****Ingredients with workplace control parameters****US**

Ingredients	Basis	Value	Control parameters	Note
Diesel fuel	ACGIH	TWA	100 mg/m3	dermatitis, A3, Skin, varies, Inhalable fraction and vapor
Naphthalene	ACGIH	TWA	10 ppm,	hematologic eff, URT irr, eye irr, eye dam, (), A4, Skin,
	ACGIH	STEL	15 ppm,	hematologic eff, URT irr, eye irr, eye dam, (), A4, Skin,
	OSHA Z-1	TWA	10 ppm, 50 mg/m3	(b),
	OSHA Z-1-A	TWA	10 ppm, 50 mg/m3	
	OSHA Z-1-A	STEL	15 ppm, 75 mg/m3	

(i) Adopted values or notations enclosed are those for which changes are proposed in the NIC

(b) The value in mg/m3 is approximate.

A3 Confirmed animal carcinogen with unknown relevance to humans

A4 Not classifiable as a human carcinogen

dermatitis Dermatitis

eye dam Eye damage

eye irr Eye irritation

hematologic eff Hematologic effects

Skin Danger of cutaneous absorption

URT irr Upper Respiratory Tract irritation

varies varies

**Immediately Dangerous to Life or Health Concentrations (IDLH)**

Substance name	CAS-No.	Control parameters	Update
Naphthalene	91-20-3	Immediately Dangerous to Life or Health Concentration Value 250 ppm	1995-03-01

**Engineering measures**

Adequate ventilation and/or engineering controls when product is heated in processing. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

**Personal protective equipment**

Respiratory protection : Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as:. Wear a supplied-air NIOSH approved respirator unless ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Air-Purifying Respirator for Organic Vapors. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.

Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the

**Diesel No. 2 Test Fuel**

Version 1.12

Revision Date 2016-05-10

	contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
Eye protection	: Eye wash bottle with pure water. Tightly fitting safety goggles.
Skin and body protection	: Choose body protection according to the amount and concentration of the dangerous substance at the work place. Wear as appropriate:. Flame retardant antistatic protective clothing. Skin should be washed after contact. Workers should wear antistatic footwear.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

**SECTION 9: Physical and chemical properties****Information on basic physical and chemical properties****Appearance**

Form	: Liquid
Physical state	: Liquid
Color	: Pale yellow to brown (if undyed), red to purple (dyed)
Odor	: Mild

**Safety data**

Flash point	: 47 °C (117 °F) minimum
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Oxidizing properties	: no
Autoignition temperature	: No data available
Molecular formula	: UVCB
Molecular weight	: Not applicable
pH	: Not applicable
Pour point	: No data available
Boiling point/boiling range	: 191 - 343 °C (376 - 649 °F)
Vapor pressure	: No data available
Relative density	: 0.87 at 16 °C (61 °F)
Density	: 0.75 - 0.90 g/cm <sup>3</sup>
Water solubility	: Negligible
Partition coefficient: n-	: No data available

**Diesel No. 2 Test Fuel**

Version 1.12

Revision Date 2016-05-10

octanol/water Viscosity, kinematic	: 2.55 cSt at 40 °C (104 °F)
Relative vapor density	: No data available
Evaporation rate	: No data available
Percent volatile	: > 99 %

**SECTION 10: Stability and reactivity**

Chemical stability : This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

**Possibility of hazardous reactions**

Conditions to avoid	: Heat, flames and sparks.
Materials to avoid	: May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.
Hazardous decomposition products	: Hydrocarbons Carbon oxides
Other data	: No decomposition if stored and applied as directed.

**SECTION 11: Toxicological information****Diesel No. 2 Test Fuel**

**Acute oral toxicity** : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

**Diesel No. 2 Test Fuel**

**Acute inhalation toxicity** : Acute toxicity estimate: 4.1 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Calculation method

**Acute dermal toxicity**

Diesel fuel : LD50 Dermal: > 4,300 mg/kg  
Species: Rabbit  
Sex: male and female  
Test substance: yes

**Skin irritation**



**Diesel No. 2 Test Fuel**

Version 1.12

Revision Date 2016-05-10

Diesel fuel : Irritating to skin.

Naphthalene No skin irritation

**Eye irritation**

Diesel fuel : No eye irritation

Naphthalene No eye irritation  
No eye irritation.

**Sensitization**

Diesel fuel : Did not cause sensitization on laboratory animals.

Naphthalene Classification: Did not cause sensitization on laboratory animals.  
Did not cause sensitization on laboratory animals.

**Repeated dose toxicity**

Diesel fuel : Species: Rat, Male and female  
Sex: Male and female  
Application Route: Dermal  
Dose: 0, 30, 125, 500 mg/kg  
Exposure time: 13 wks  
Number of exposures: daily, 5 days/week  
NOEL: 30 mg/kg  
Method: OECD Guideline 411  
Target Organs: Thymus, Liver, Bone marrow  
Information given is based on data obtained from similar substances.

Species: Rat, Male and female  
Sex: Male and female  
Application Route: inhalation (dust/mist/fume)  
Dose: 0, 0.35, 0.88, 1.71 mg/l  
Exposure time: 13 wks  
Number of exposures: Twice/wk  
NOEL: > 1.71 mg/l  
Method: OECD Guideline 413

**Carcinogenicity**

Diesel fuel : Species: Mouse  
Sex: male  
Dose: 0, 25 ul  
Exposure time: lifetime  
Number of exposures: 3 times/wk  
Remarks: Moderate dermal carcinogen

Naphthalene Species: Mouse  
Sex: male  
Dose: 10, 30 ppm  
Exposure time: 105 weeks  
Number of exposures: 6 hours/day, 5 days/week  
Test substance: yes  
Print Date: No information available.  
Remarks: No evidence of carcinogenicity

**Diesel No. 2 Test Fuel**

Version 1.12

Revision Date 2016-05-10

Species: Mouse  
 Sex: female  
 Dose: 10, 30 ppm  
 Exposure time: 105 weeks  
 Number of exposures: 6 hours/day, 5 days/week  
 Test substance: yes  
 Print Date: No information available.  
 Remarks: increased incidence of alveolar/bronchiolar adenomas

Species: Rat  
 Sex: male and female  
 Dose: 10, 30, 60 ppm  
 Exposure time: 105 weeks  
 Number of exposures: 6 hours/day, 5 days/week  
 Test substance: yes  
 Print Date: No information available.  
 Remarks: nose respiratory epithelial adenoma, increased incidence of olfactory neuroblastomas

**Developmental Toxicity**

Diesel fuel

: Species: Rat  
 Application Route: Inhalation  
 Dose: 0, 86.9, 408.8 ppm  
 Number of exposures: 6 h/d  
 Test period: GD 6-15  
 Method: OECD Guideline 414  
 NOAEL Teratogenicity: 408.8 ppm  
 NOAEL Maternal: 408.8 ppm  
 Information given is based on data obtained from similar substances.

Species: Rat  
 Application Route: Dermal  
 Dose: 30, 125, 500, 1000 mg/kg  
 Exposure time: daily  
 Test period: GD 0-20  
 Method: OECD Guideline 414  
 NOAEL Teratogenicity: 125 mg/kg  
 Information given is based on data obtained from similar substances.

Naphthalene

Species: Rabbit  
 Application Route: oral gavage  
 Dose: 40, 200, 400 mg/kg  
 Test period: 29 d, GD 6-18  
 NOAEL Teratogenicity: 400 mg/kg

**Diesel No. 2 Test Fuel  
Aspiration toxicity**

: May be fatal if swallowed and enters airways.

**CMR effects**

Diesel fuel

: Carcinogenicity: Limited evidence of carcinogenicity in animal studies  
 Teratogenicity: Animal testing did not show any effects on fetal development.

**Diesel No. 2 Test Fuel**

Version 1.12

Revision Date 2016-05-10

Naphthalene

Carcinogenicity: Limited evidence of carcinogenicity in animal studies

**Diesel No. 2 Test Fuel****Further information**

: Solvents may degrease the skin.

**SECTION 12: Ecological information****Toxicity to fish**

Diesel fuel

: LL50: 3.2 mg/l  
Exposure time: 96 h  
Species: Menidia beryllina (Silverside)  
semi-static test Method: EPA/600/4-90/027

Naphthalene

LC50: 3.2 mg/l  
Exposure time: 96 h  
Species: Pimephales promelas (fathead minnow)**Toxicity to daphnia and other aquatic invertebrates**

Diesel fuel

: EC50: 68 mg/l  
Exposure time: 48 h  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 202

Naphthalene

LC50: 2.16 mg/l  
Exposure time: 48 h  
Species: Daphnia magna (Water flea)**Toxicity to algae**

Diesel fuel

: EbC50: 10 mg/l  
Exposure time: 72 h  
Species: Raphidocellus subcapitata (algae)  
static test Analytical monitoring: no  
Method: OECD Test Guideline 201

Naphthalene

EC50: 2.96 mg/l  
Exposure time: 48 h  
Species: Selenastrum capricornutum (algae)**Biodegradability**

Diesel fuel

: aerobic  
Result: Not readily biodegradable.  
57.5 %  
Testing period: 28 d  
Method: OECD Test Guideline 301F**Ecotoxicology Assessment**

**Diesel No. 2 Test Fuel**

Version 1.12

Revision Date 2016-05-10

Acute aquatic toxicity Diesel fuel	: Toxic to aquatic life.
Naphthalene	: Very toxic to aquatic life.
Chronic aquatic toxicity Diesel fuel	: Toxic to aquatic life with long lasting effects.
Naphthalene	: Very toxic to aquatic life with long lasting effects.
Results of PBT assessment Diesel fuel	: Non-classified PBT substance, Non-classified vPvB substance
Additional ecological information	: Toxic to aquatic life with long lasting effects.

**SECTION 13: Disposal considerations**

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product	: The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14: Transport information**

**The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).**

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

**US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)**  
UN1202, DIESEL FUEL, 3, III

**IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)**  
UN1202, DIESEL FUEL, 3, III, (47 °C), MARINE POLLUTANT, (DIESEL FUEL)

**IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)**

**Diesel No. 2 Test Fuel**

Version 1.12

Revision Date 2016-05-10

UN1202, DIESEL FUEL, 3, III

**ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))**

UN1202, DIESEL FUEL, 3, III, (D/E), ENVIRONMENTALLY HAZARDOUS, (DIESEL FUEL)

**RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))**

UN1202, DIESEL FUEL, 3, III, ENVIRONMENTALLY HAZARDOUS, (DIESEL FUEL)

**ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)**

UN1202, DIESEL FUEL, 3, III, ENVIRONMENTALLY HAZARDOUS, (DIESEL FUEL)

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code****SECTION 15: Regulatory information****National legislation**

CERCLA Reportable Quantity : Calculated RQ exceeds reasonably attainable upper limit.  
Naphthalene

SARA 302 Reportable Quantity : This material does not contain any components with a SARA 302 RQ.

SARA 302 Threshold Planning Quantity : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 304 Reportable Quantity : This material does not contain any components with a section 304 EHS RQ.

SARA 313 Ingredients : The following components are subject to reporting levels established by SARA Title III, Section 313:

: Naphthalene - 91-20-3

**Clean Air Act**

Ozone-Depletion Potential : This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

**Diesel No. 2 Test Fuel**

Version 1.12

Revision Date 2016-05-10

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):  
: Naphthalene - 91-20-3

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

**US State Regulations****Pennsylvania Right To Know**

: Diesel fuel - 68476-34-6  
Naphthalene - 91-20-3

**New Jersey Right To Know**

: Diesel fuel - 68476-34-6  
Naphthalene - 91-20-3

**California Prop. 65  
Ingredients**

: WARNING! This product contains a chemical known in the State of California to cause cancer.

**Notification status**

Europe REACH : This mixture contains only ingredients which have been registered according to Regulation (EU) No. 1907/2006 (REACH).

United States of America TSCA : On TSCA Inventory

Canada DSL : All components of this product are on the Canadian DSL

Australia AICS : On the inventory, or in compliance with the inventory

New Zealand NZIoC : On the inventory, or in compliance with the inventory

Japan ENCS : On the inventory, or in compliance with the inventory

Korea KECI : On the inventory, or in compliance with the inventory

Philippines PICCS : On the inventory, or in compliance with the inventory

China IECSC : On the inventory, or in compliance with the inventory


**Diesel No. 2 Test Fuel**

Version 1.12

Revision Date 2016-05-10

**SECTION 16: Other information**

**NFPA Classification** : Health Hazard: 2  
Fire Hazard: 2  
Reactivity Hazard: 0

**Further information**

Legacy SDS Number : CPC00523

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical	TWA	Time Weighted Average

**Diesel No. 2 Test Fuel**

Version 1.12

Revision Date 2016-05-10

	Substances in China		
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		