

MATERIAL SAFETY DATA SHEET

ECP Incorporated
4700 South Central Avenue
Chicago, IL. 60638
TELEPHONE 708-496-7350
EMERGENCY 800-424-9300

HMIS HAZARD RATING	
HEALTH	1
FIRE	2
REACTIVITY	0
PERSONAL PROTECTION	C

DATE OF PREPARATION
SEPTEMBER 11, 2001
BY TECHNICAL SERVICES

DATE OF REVIEW/UPDATE
JUNE 14, 2006

SECTION 1 - PRODUCT IDENTIFICATION

ITEM NUMBER
4763
ITEM DESCRIPTION
PRO PAINT SHIELD CLEANER
PRODUCT NAME
PROTECTOR PAINT SHIELD CLEANER
PRODUCT CLASS
Automotive Wax/Polish

SECTION 2 - HAZARDOUS INGREDIENTS

INGREDIENT	MAX. % BY WT.	TLV ¹	PEL ²
CAS NUMBER			
KAOLIN CLAY	10-14	10mg/m3 dust	unknown
66402-68-4			
PETROLEUM DISTILLATES	5-7	100ppm	100ppm
64742-47-8			
PETROLEUM DISTILLATES	15-17	unknown	500ppm
8008-20-6			
Listed as IARC, NTP, or OSHA Carcinogen: None			

SECTION 3 - PHYSICAL CHARACTERISTICS

BOILING POINT: 212F
VAPOR PRESSURE(mmHg @ 68F) 3.4
VAPOR DENSITY(AIR=1) >1
SOLUBILITY IN WATER: NEGLIGIBLE
SPECIFIC GRAVITY: 1.01+/-0.05
% VOLATILE (VOLUME) 75+/-1.0
MELTING POINT: NOT APPLICABLE
EVAPORATION RATE(WATER=1) 1
APPEARANCE AND ODOR: YELLOW CREAMY LIQUID, SOLVENT

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT / METHOD: 170 F / TCC
FLAMMABLE LIMITS: LEL: 0.6 UEL: 7.0
EXTINGUISHING MEDIA: Water fog, dry chemicals or carbon dioxide.
SPECIAL FIRE FIGHTING PROCEDURES:
Full protective equipment including self contained breathing apparatus for confined areas.
UNUSUAL FIRE AND EXPLOSION HAZARDS:
Vapors are heavier than air. Treat as petroleum fire.

SECTION 5 - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE:

EYE: Irritation of eyes. Prolonged contact can cause severe irritation, redness, tearing, blurred vision.

SKIN: Dryness, redness and itching or a burning sensation.

INHALATION: Irritation of respiratory system headache, dizziness, nausea, fatigue and loss of coordination.

INGESTION: Gastrointestinal irritation, vomiting, and diarrhea. Aspiration can cause chemical pneumonitis that can be fatal.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Dermatitis. Alcohol consumption may increase adverse affects.

EMERGENCY AND FIRST AID PROCEDURES:

INHALATION Remove exposure. Restore breathing. Keep warm and quite.

SKIN Wash affected area with soap and water. Remove contaminated clothing and laundry before reuse.

EYES Flush with large amounts of water. Get medical attention.

IF SWALLOWED Never give anything by mouth to an unconscious person.

DO NOT INDUCE VOMITING. Seek medical attention.

SECTION 6 - REACTIVITY DATA

STABILITY: Stable

INCOMPATIBILITY: Strong oxidizers

HAZARDOUS DECOMPOSITION PRODUCTS: Various hydrocarbons of incomplete combustion.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 7 - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR LEAKED:

Remove all sources of ignition. Contain spill. Ventilate and remove with inert absorbent.

WASTE DISPOSAL METHOD:

Waste from this product is hazardous (D001) as defined by the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Dispose of in accordance with federal, state and local regulations.

NOTE: Empty containers less than 110 gallons of D001 are not hazardous waste if as much of the product has been consumed as practical and less than 1 inch or 3% (by weight) of residue remain. (40CFR, 261.7)

SECTION 8 - SPECIAL PROTECTION INFORMATION

VENTILATION:

Use only with adequate ventilation. Avoid breathing vapor or mist.

Local exhaust preferred.

RESPIRATORY PROTECTION:

Properly fitted NIOSH/MSHA approved respirator for ingredients found in (SECTION 2) if TLV is exceeded.

SKIN PROTECTION:

Gloves rated for protection against ingredients in (SECTION 2).

EYE PROTECTION:

Safety glasses with side shields or chemical goggles.

=====

SECTION 9 - PRECAUTIONARY INFORMATION

PRECAUTIONS TO BE TAKEN IN STORING AND HANDLING:

Contents may burn. Keep away from any heat or spark source. Do not smoke. Empty containers can contain explosive vapors. Never use a torch to cut or weld on or near container. Never wear oil soaked clothing. Launder or dry-clean before wearing. Discard oil soaked shoes. Affix proper warning labels on containers in accordance with 29CFR 1010.1200.

=====

SECTION 10 - REGULATORY INFORMATION

D.O.T. REQUIREMENTS (49CFR 172.101)

Not regulated when shipped in quantities less than 119 gallons. If shipped in quantities of more than 119 gallons, or if shipped by vessel or aircraft use the following Proper Shipping Description (49CFR 173.120):

COMBUSTIBLE LIQUID, N.O.S., 3, UN1268, PGIII (NAPHTHA SOLVENT)

RQ (REPORTABLE QUANTITY) 49CFR 172.101

COMPONENT	RQ (lb.)	FOR THIS PRODUCT

None		

TSCA (Toxic Substances Control Act) Status

The intentional ingredients of this product are listed.

CERCLA RQ - 40CFR 302.4

None

SARA 302 COMPONENTS - 40CFR 355 Appendix A

None

SECTION 311/312 HAZARD CLASS - 40CFR 370.2

Immediate	(X)	Reactive	()
Delayed	(X)	Sudden Release of Pressure	()
Fire	(X)		

SARA 313 COMPONENTS - 40CFR 372.65

None

WORKPLACE HAZARDOUS INFORMATION SYSTEM (WHMIS)

INGREDIENT	MAX. % BY WT.	LD50	LC50
PETROLEUM DISTILLATES	24	5000mg/kg oral-rat	3400ppm/4hr inhl-rat

=====

The information contained herein is based on data we believe to be correct. Any use of the product that is not in conformance with this MSDS or which involves using the product in combination with any other product or any process is the responsibility of the user.

¹ ACGIH

² OSHA