# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 08/08/2014 : Version:

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Mixture

Trade name : FVP NON-CHLORINATED BRAKE CLEANER NON-VOC 15 OZ.

Product code : FVPNCBC-15

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Brake Parts Cleaner

### 1.3. Details of the supplier of the safety data sheet

**Factory Motor Parts** 

1380 Corporate center Curve Ste. 200

Eagan, MN 55121 (866) 387-3343

### 1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### Classification (GHS-US)

Flam. Aerosol 2 H223 Compressed gas H280 Acute Tox. 3 (Oral) H301 Acute Tox. 3 (Dermal) H311 Skin Irrit. 2 H315 Eye Irrit. 2A H319 Repr. 2 H361 STOT SE 1 H370 STOT SE 3 H336 STOT RE 2 H373

Full text of H-phrases: see section 16

### 2.2. Label elements

# **GHS-US** labeling

Hazard pictograms (GHS-US)



GHS02

 $\Diamond$ 

GHS04





GHS07



Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H223 - Flammable aerosol

H280 - Contains gas under pressure; may explode if heated H301+H311 - Toxic if swallowed or in contact with skin

H315 - Causes skin irritation

H319 - Causes serious eye irritation H336 - May cause drowsiness or dizziness

H361 - Suspected of damaging fertility or the unborn child

H370 - Causes damage to organs

H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) : P201 - Obtain special instructions

P202 - Do not handle until all safety precautions have been read and understood P210

Keep away from heat, sparks, open flames, hot surfaces.
 No smoking
 Do not spray on an open flame or other ignition source

P251 - Pressurized container: Do not pierce or burn, even after use P260 - Do not breathe dust, fumes, gas, mist, vapor spray P261 - Avoid breathing dust, fumes, gas, mist, vapor spray P264 - Wash affected areas thoroughly after handling P270 - Do not eat, drink or smoke when using this product P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves, protective clothing, eye protection, face protection P301+P310 - If swallowed: Immediately call a poison control center, doctor, physician,

P302+P352 - If on skin: Wash with plenty of soap and water P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for

05/12/2014 EN(密納的9US) 1/13

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P307+P311 - If exposed: Call a poison center/doctor

P308+P313 - If exposed or concerned: Get medical advice/attention P312 - Call a POISON CONTROL CENTER, doctor, if you feel unwell.

P314 - Get medical advice/attention if you feel unwell

P321 - Specific treatment: See section 4.1 on SDS

P330 - Rinse mouth

P332+P313 - If skin irritation occurs: Get medical advice/attention P337+P313 - If eye irritation persists: Get medical advice/attention

P361 - Take off immediately all contaminated clothing

P362 - Take off contaminated clothing and wash before reuse

P363 - Wash contaminated clothing before reuse

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P405 - Store locked up

P410+P403 - Protect from sunlight. Store in a well-ventilated place

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with

local, regional, national, international regulations.

### 2.3. Other hazards

Other hazards not contributing to the classification

: Contains gas under pressure; may explode if heated.

### 2.4. Unknown acute toxicity (GHS-US)

No data available

# **SECTION 3: Composition/information on ingredients**

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	<b>%</b>	Classification (GHS-US)
Methanol	(CAS No) 67-56-1	30 - 50	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:dust,mist), H331 STOT SE 1, H370
Acetone	(CAS No) 67-64-1	10 - 30	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Toluene	(CAS No) 108-88-3	10 - 30	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
Heptane, Branched Cyclic	(CAS No) 426260-76-6	17.4528 - 18.18	Flam. Liq. 1, H224 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Heptane	(CAS No) 142-82-5	4.545 - 8.181	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Carbon Dioxide, Liquefied, Under Pressure	(CAS No) 124-38-9	5 - 10	Compressed gas, H280

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER or doctor/physician.

First-aid measures after inhalation : Cough. Remove to fresh air and keep at rest in a position comfortable for breathing. Call a

POISON CENTER/doctor/physician if you feel unwell.

First-aid measures after skin contact : Rinse skin with water/shower. Immediately call a POISON CENTER or doctor/physician.

Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water.

Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact

: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. Immediately call a POISON CENTER or doctor/physician. Obtain medical attention if pain, blinking or redness persist. Direct contact with the eyes is likely to be irritating.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Immediately call a POISON CENTER or doctor/physician.

05/12/2014 EN (English US) 2/13

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Suspected of damaging fertility or the unborn child. Causes damage to organs.

Symptoms/injuries after inhalation : May cause respiratory irritation. Shortness of breath. May cause drowsiness or dizziness.

Symptoms/injuries after skin contact : Repeated exposure to this material can result in absorption through skin causing significant

health hazard. Toxic in contact with skin. Causes skin irritation.

Symptoms/injuries after eye contact : Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue.

Symptoms/injuries after ingestion : Toxic if swallowed. Swallowing a small quantity of this material will result in serious health

hazard

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

# **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable aerosol.

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns

and injuries

### 5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment. DO NOT fight fire when fire

reaches explosives. Evacuate area.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Other information : Aerosol Level 2.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : No naked lights. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove

ignition sources. Use special care to avoid static electric charges.

### 6.1.1. For non-emergency personnel

Protective equipment : Safety glasses. Gloves.

Emergency procedures : Evacuate unnecessary personnel.

### 6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust,fume,gas,mist,vapor spray.

Emergency procedures : Ventilate area.

# 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment : Dam up the liquid spill. Plug the leak, cut off the supply. Contain released substance, pump into

suitable containers.

Methods for cleaning up : Store away from other materials.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

### SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Hazardous waste due to potential risk of explosion. Pressurized container: Do not pierce or burn,

even after us

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not spray on an open flame or other ignition source. Obtain special instructions. Do not handle until all safety precautions have been read and understood. Avoid breathing dust, fumes, gas, mist, vapor spray. Use only outdoors or in a well-ventilated area. Do not

breathe dust, fumes, gas, mist, vapor spray.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

Wash affected areas thoroughly after handling. Wash hands and other exposed areas with mild

soap and water before eating, drinking or smoking and when leaving work.

05/12/2014 EN (English US) 3/13

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

7.2.	for safe storage.		

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Do not expose to

temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place. Keep container tightly closed.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

Storage area : Store in a well-ventilated place.

### 7.3. Specific end use(s)

Follow Label Directions.

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

Benzene (71-43-2)		
USA ACGIH	ACGIH TWA (ppm)	1 ppm
USA ACGIH	ACGIH STEL (ppm)	5 ppm
USA ACGIH	ACGIH Ceiling (ppm)	25 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	1 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	5 ppm

Toluene (108-88-3)		
USA ACGIH	ACGIH TWA (mg/m³)	75 mg/m³
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm

Heptane (142-82-5)		
USA ACGIH	ACGIH TWA (ppm)	400 ppm
USA ACGIH	ACGIH STEL (ppm)	400 ppm

Heptane, Branched Cyclic (426260-76-6)		
USA ACGIH	ACGIH TWA (ppm)	400 ppm
USA ACGIH	ACGIH STEL (ppm)	500 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	500 ppm

Carbon Dioxide, Liquefied, Under Pressure (124-38-9)		
USA ACGIH	ACGIH TWA (mg/m³)	9000 mg/m³
USA ACGIH	ACGIH TWA (ppm)	5000 ppm
USA ACGIH	ACGIH STEL (mg/m³)	54000
USA ACGIH	ACGIH STEL (ppm)	30000 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	9000 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	5000 ppm

Methanol (67-56-1)		
USA ACGIH	ACGIH TWA (mg/m³)	262 mg/m³
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (mg/m³)	328 mg/m³
USA ACGIH	ACGIH STEL (ppm)	250 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm

Acetone (67-64-1)		
USA ACGIH	ACGIH TWA (mg/m³)	1188 mg/m³
USA ACGIH	ACGIH TWA (ppm)	500 ppm
USA ACGIH	ACGIH STEL (mg/m³)	1782 mg/m³

05/12/2014 EN (English US) 4/13

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acetone (67-64-1)		
USA ACGIH	ACGIH STEL (ppm)	750 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	2400 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm

### 8.2. Exposure controls

Appropriate engineering controls : Local exhaust ventilation, vent hoods.

Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.





Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or safety glasses. Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is

recommended.

Other information : Do not eat, drink or smoke during use.

### SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Gas
Appearance : Liquid.

Color : Colourless to light yellow.
Odor : Solvent-like odour.
Odor threshold : No data available
pH : No data available
Relative evaporation rate (butyl acetate=1) : No data available

Melting point : -95 °C (Lowest Component)

Freezing point : No data available

Boiling point : 56 °C (Lowest Component)

Flash point : -18 °C (Lowest Component)

Auto-ignition temperature : 465 °C (Lowest Component)

Decomposition temperature : No data available
Flammability (solid, gas) : No data available
Vapor pressure : No data available
Relative vapor density at 20 °C : No data available

Relative density : 0.78

Solubility : Moderately soluble in water.

Log Pow : No data available
Log Kow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available

Explosive properties : Heating may cause a fire or explosion.

Oxidizing properties : No data available Explosive limits : No data available

9.2. Other information

VOC content : 69.3 %
Gas group : Liquefied gas

# **SECTION 10: Stability and reactivity**

# 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

05/12/2014 EN (English US) 5/13

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.3. Possibility of hazardous reactions

Not established.

# 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

### 10.5. Incompatible materials

Strong acids. Strong bases.

Toluene (108-88-3)
IARC group

### 10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

# **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

Acute toxicity : Toxic if swallowed. Toxic in contact with skin

Acute toxicity	: Toxic if swallowed. Toxic in contact with skin.
Benzene (71-43-2)	
LD50 oral rat	> 930 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; > 2000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	> 8240 mg/kg (Rabbit; Experimental value; 21 CFR 191.10; > 9.4; Rabbit)
LC50 inhalation rat (mg/l)	43.767 mg/l/4h (Rat; Experimental value)
LC50 inhalation rat (ppm)	13700 ppm/4h (Rat; Experimental value)
Toluene (108-88-3)	
LD50 oral rat	5580 mg/kg body weight (Rat; Equivalent or similar to OECD 401; Literature study; 5580 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	> 5000 mg/kg body weight LD50 quoted as 14.1 mL/kg (12267 mg/kg using density of 0.87)
LC50 inhalation rat (mg/l)	> 28.1 mg/l/4h (Rat; Air, Literature study)
Heptane (142-82-5)	
LD50 oral rat	> 15000 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; >5000 mg/kg bodyweight; Rat; Read-across)
LD50 dermal rabbit	> 3160 mg/kg (Rabbit; Literature study; Equivalent or similar to OECD 402; >2000 mg/kg bodyweight; Rabbit; Read-across)
LC50 inhalation rat (mg/l)	103 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	25000 ppm/4h (Rat; Literature study)
Heptane, Branched Cyclic (426260-76-6)	
LD50 oral rat	> 15000 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; >5000 mg/kg bodyweight; Rat; Read-across)
LD50 dermal rabbit	> 3160 mg/kg (Rabbit; Literature study; Equivalent or similar to OECD 402; >2000 mg/kg bodyweight; Rabbit; Read-across)
LC50 inhalation rat (mg/l)	103 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	25000 ppm/4h (Rat; Literature study)
Methanol (67-56-1)	
LD50 oral rat	>= 2528 mg/kg body weight application as 50% aqueous solution
LD50 dermal rabbit	17100 mg/kg corresponding to 20 ml/kg bw according to the authors
LC50 inhalation rat (mg/l)	128.2 mg/l/4h Air
Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	20000 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402)
LC50 inhalation rat (mg/l)	71 mg/l/4h (Rat; Experimental value; 76 mg/l/4h; Rat; Experimental value)
LC50 inhalation rat (ppm)	30000 ppm/4h (Rat; Experimental value)
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Benzene (71-43-2)	
IARC group	1

05/12/2014 EN (English US) 6/13

3

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

: Suspected of damaging fertility or the unborn child. Reproductive toxicity

Specific target organ toxicity (single exposure) : Causes damage to organs. May cause drowsiness or dizziness.

Specific target organ toxicity (repeated

Symptoms/injuries after inhalation

Symptoms/injuries after skin contact

exposure)

: May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

Potential Adverse human health effects and symptoms

: Based on available data, the classification criteria are not met. Toxic if swallowed. Toxic in contact with skin.

: May cause respiratory irritation. Shortness of breath. May cause drowsiness or dizziness.

: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Toxic in contact with skin. Causes skin irritation.

: Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue. Symptoms/injuries after eye contact

Symptoms/injuries after ingestion : Toxic if swallowed. Swallowing a small quantity of this material will result in serious health

hazard.

# **SECTION 12: Ecological information**

#### 12.1. **Toxicity**

Benzene (71-43-2)	
LC50 fish 1	5.3 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 1	18 mg/l (24 h; Daphnia magna)
LC50 fish 2	15.1 mg/l (96 h; Pimephales promelas)
EC50 Daphnia 2	10 mg/l (48 h; Daphnia magna)
TLM fish 1	22.5 mg/l (96 h; Lepomis macrochirus; Soft water)
TLM fish 2	32 mg/l (96 h; Pimephales promelas; Hard water)
Threshold limit algae 1	100 mg/l (72 h; Pseudokirchneriella subcapitata; GLP)
Threshold limit algae 2	50 mg/l (24 h; Phaeodactylum; Photosynthesis)

Acetone (67-64-1)	
TLM fish 1	13000 ppm (96 h; Gambusia affinis; Turbulent water)
TLM fish 2	> 1000 ppm (96 h; Pisces)
Threshold limit other aquatic organisms 1	3000 mg/l (Plankton)
Threshold limit other aquatic organisms 2	28 mg/l (Protozoa)
Threshold limit algae 1	7500 mg/l (Scenedesmus quadricauda; pH = 7)
Threshold limit algae 2	3400 mg/l (48 h: Chlorella sp.)

Toluene (108-88-3)	
LC50 fish 1	24 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 1	84 mg/l (24 h; Daphnia magna; Locomotor effect)
LC50 fish 2	13 mg/l (96 h; Lepomis macrochirus)
EC50 Daphnia 2	11.5 - 19.6 mg/l (48 h; Daphnia magna)
Threshold limit algae 1	> 400 mg/l (168 h; Scenedesmus quadricauda; Toxicity test)
Threshold limit algae 2	105 mg/l (192 h; Microcystis aeruginosa)

Heptane (142-82-5)	
LC50 fish 1	375 mg/l (96 h; Tilapia mossambica; Nominal concentration)
LC50 other aquatic organisms 1	> 1000 mg/l (96 h)
EC50 Daphnia 1	1.5 mg/l (48 h; Daphnia magna)
LC50 fish 2	> 100 mg/l (96 h; Oncorhynchus kisutch)
TLM fish 1	4924 mg/l (48 h; Gambusia affinis)
Threshold limit other aquatic organisms 1	> 1000 mg/l (96 h)
Threshold limit algae 1	> 200 mg/l (Scenedesmus quadricauda; Toxicity test)
Threshold limit algae 2	1.5 mg/l (8 h; Algae; Photosynthesis)

Carbon Dioxide, Liquefied, Under Pressure (124-38-9)	
LC50 fish 1	35 mg/l (96 h; Salmo gairdneri (Oncorhynchus mykiss); Lethal)
LC50 fish 2	60 - 240 mg/l (12 h; Salmo gairdneri (Oncorhynchus mykiss); Lethal)

Methanol (67-56-1)	
LC50 fish 1	15400 mg/l (96 h; Lepomis macrochirus; Lethal)
EC50 Daphnia 1	> 10000 mg/l (48 h; Daphnia magna; Lethal)
LC50 fish 2	10800 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 2	24500 mg/l (48 h; Daphnia magna; Locomotor effect)
Threshold limit other aquatic organisms 1	6600 mg/l (16 h; Pseudomonas putida)
Threshold limit algae 1	530 mg/l (192 h; Microcystis aeruginosa)

05/12/2014 EN (English US) 7/13

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanol (67-56-1)		
Threshold limit algae 2	8000 mg/l (168 h; Scenedesmus quadricauda)	
•	,	
Acetone (67-64-1) LC50 fish 1	6210 mg/l (06 h; Dimonholog promolog; Nominal concentration)	
	6210 mg/l (96 h; Pimephales promelas; Nominal concentration)	
EC50 Daphnia 1	8800 mg/l (48 h; Daphnia pulex)	
LC50 fish 2	5540 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)	
TLM fish 1	13000 ppm (96 h; Gambusia affinis; Turbulent water)	
TLM fish 2	> 1000 ppm (96 h; Pisces)	
Threshold limit other aquatic organisms 1	3000 mg/l (Plankton)	
Threshold limit other aquatic organisms 2	28 mg/l (Protozoa)	
Threshold limit algae 1	7500 mg/l (Scenedesmus quadricauda; pH = 7)	
Threshold limit algae 2	3400 mg/l (48 h; Chlorella sp.)	
2.2. Persistence and degradability		
<b>FVP NON-CHLORINATED BRAKE CLEANE</b>	R NON-VOC 15 OZ.	
Persistence and degradability	Not established.	
Benzene (71-43-2)		
Persistence and degradability	Readily biodegradable in water. Ozonation in water. Forming sediments in water.	
reisisterice and degradability	Biodegradable in the soil. Low potential for adsorption in soil. Photolysis in the air.	
Biochemical oxygen demand (BOD)	2.18 g O <sub>2</sub> /g substance	
Chemical oxygen demand (COD)	2.15 g O <sub>2</sub> /g substance	
ThOD	3.10 g O <sub>2</sub> /g substance	
BOD (% of ThOD)	0.70 % ThOD	
	0.10 % THOS	
Acetone (67-64-1)		
Persistence and degradability	Not established.	
Toluene (108-88-3)		
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.	
Biochemical oxygen demand (BOD)	2.15 g O <sub>2</sub> /g substance	
Chemical oxygen demand (COD)	2.52 g O <sub>2</sub> /g substance	
ThOD	3.13 g O <sub>2</sub> /g substance	
BOD (% of ThOD)	0.69 % ThOD	
Heptane (142-82-5)		
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Adsorbs into the soil.	
Biochemical oxygen demand (BOD)	1.92 g O <sub>2</sub> /g substance	
Chemical oxygen demand (COD)	0.06 g O <sub>2</sub> /g substance	
ThOD	3.52 g O <sub>2</sub> /g substance	
BOD (% of ThOD)	> % ThOD (5 day(s)) > 0.5	
BOD (% OF THOD)	> % 1110D (3 day(s)) > 0.3	
Heptane, Branched Cyclic (426260-76-6)		
Persistence and degradability	May cause long-term adverse effects in the environment.	
Carbon Dioxide, Liquefied, Under Pressure	e (124-38-9)	
Persistence and degradability	Biodegradability: not applicable. Not applicable (gas).	
Biochemical oxygen demand (BOD)	Not applicable	
Chemical oxygen demand (COD)	Not applicable	
ThOD	Not applicable	
BOD (% of ThOD)	Not applicable	
Methanol (67-56-1)	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.	
Persistence and degradability	, , , , , , , , , , , , , , , , , , , ,	
Biochemical oxygen demand (BOD)	0.6 - 1.12 g O <sub>2</sub> /g substance	
Chemical oxygen demand (COD)	1.42 g O <sub>2</sub> /g substance	
ThOD  POD (% of ThOD)	1.5 g O <sub>2</sub> /g substance	
BOD (% of ThOD)	U.O 70 IIIUU	
Acetone (67-64-1)		
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. No (test) data on mobility of the substance available. Not	
Biochemical oxygen demand (BOD)	establishedg substance	
Chemical oxygen demand (COD)	1.92 g O <sub>2</sub> /g substance	
ThOD	2.20 g O <sub>2</sub> /g substance	

05/12/2014 EN (English US) 8/13

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Acetone (67-64-1)

Other information

BOD (% of ThOD) (20 day(s)) 0.872

12.3.	Bioaccumulat	ive po	tential
-------	--------------	--------	---------

<b>FVP NON-CHLORINATED BRAKE CLEAN</b>	IER NON-VOC 15 OZ.
Bioaccumulative potential	Not established.
Benzene (71-43-2)	
BCF fish 1	19 Salmo gairdneri (Oncorhynchus mykiss)
BCF fish 2	< 10 (3 days; Leuciscus idus)
BCF other aquatic organisms 1	30 (24 h; Chlorella sp.; Fresh weight)
Log Pow	2.13 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
Acetone (67-64-1)	
Bioaccumulative potential	Not established.
Toluene (108-88-3)	
BCF fish 1	13.2 (Anguilla japonica)
BCF fish 2	90 (72 h; Leuciscus idus)
BCF other aquatic organisms 1	380 (24 h; Chlorella sp.; Fresh weight)
BCF other aquatic organisms 2	4.2 (Mytilus edulis; Fresh weight)
Log Pow	2.73 (Experimental value; Other; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
Heptane (142-82-5)	
BCF other aquatic organisms 1	552
Log Pow	4.66 (Experimental value; 4.5; Literature)
Bioaccumulative potential	Potential for bioaccumulation (4 ≥ Log Kow ≤ 5).
Heptane, Branched Cyclic (426260-76-6)	
Bioaccumulative potential	Not established.
·	
Carbon Dioxide, Liquefied, Under Pressu	
Log Pow Bioaccumulative potential	0.83 (Experimental value)
·	Bioaccumulation: not applicable.
Methanol (67-56-1)	40/70/11
BCF fish 1	< 10 (72 h; Leuciscus idus)
BCF fish 2	1 (72 h; Cyprinus carpio; Blood)
Log Pow	-0.77 (Experimental value; Other)  Low potential for bioaccumulation (BCF < 500).
Bioaccumulative potential	Low potential for bloaccumulation (BCF < 500).
Acetone (67-64-1)	0.00 (0)
BCF fish 1	0.69 (Pisces)
BCF other aquatic organisms 1	3
Log Pow Bioaccumulative potential	-0.24 (Test data)  Not bioaccumulative. Not established.
·	Not bloaccumulative. Not established.
12.4. Mobility in soil	
Benzene (71-43-2)	
Surface tension	0.029 N/m (20 °C)
Toluene (108-88-3)	
Surface tension	0.03 N/m (20 °C)
Hentone (442.92.5)	
Heptane (142-82-5) Surface tension	0.020 N/m (20 °C)
	0.020 (Will (20 O)
Methanol (67-56-1)	
Surface tension	0.023 N/m (20 °C)
Acetone (67-64-1)	
Curface tension	0.0237 N/m (20 °C)
Surface tension	0.0207 14/11 (20 0)

05/12/2014 EN (English US) 9/13

: Avoid release to the environment.

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### **SECTION 13: Disposal considerations**

Waste treatment methods

Dispose in a safe manner in accordance with local/national regulations. Container under Waste disposal recommendations

pressure. Do not drill or burn even after use. Dispose of contents/container to appropriate waste

disposal facility, in accordance with local, regional, national, international regulations.

Additional information : Flammable vapors may accumulate in the container.

Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

### **SECTION 14: Transport information**

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): UN1950, Aerosols, 2.1, Limited Quantity ICAO/IATA (air): UN1950, Aerosols, 2.1, Limited Quantity IMO/IMDG (water): UN1950, Aerosols, 2.1, Limited Quantity

N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols. Special Provisions:

**UN** proper shipping name

Proper Shipping Name (DOT) : Aerosols

flammable, (each not exceeding 1 L capacity)

Department of Transportation (DOT) Hazard

Classes

Hazard labels (DOT)

: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

: 2.1 - Flammable gas



DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

DOT Packaging Exceptions (49 CFR 173.xxx) 306 DOT Packaging Non Bulk (49 CFR 173.xxx) : None DOT Packaging Bulk (49 CFR 173.xxx) : None

14.3. Additional information

Other information : No supplementary information available.

### **Overland transport**

No additional information available

Transport by sea

**DOT Vessel Stowage Location** : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

: 48 - Stow "away from" sources of heat,87 - Stow "separated from" Class 1 (explosives) except DOT Vessel Stowage Other

Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 75 kg (49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

### SECTION 15: Regulatory information

### 15.1. US Federal regulations

FVP NON-CHLORINATED BRAKE CLEANER NON-VOC 15 OZ.		
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard	

Fire hazard Immediate (acute) health hazard

Sudden release of pressure hazard

Toluene (108-88-3)

Listed on United States SARA Section 313

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Delayed (chronic) health hazard SARA Section 311/312 Hazard Classes Fire hazard

Immediate (acute) health hazard

05/12/2014 EN (English US) 10/13

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Heptane, Branched Cyclic (426260-76-6)	
Not listed on the United States TSCA (Toxic Sul	bstances Control Act) inventory
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
Methanol (67-56-1)	
Listed on United States SARA Section 313 Listed on the United States TSCA (Toxic Substa	ances Control Act) inventory
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard
Acetone (67-64-1)	
Listed on the United States TSCA (Toxic Substa	ances Control Act) inventory
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard Delayed (chronic) health hazard

# 15.2. International regulations

### **CANADA**

FVP NON-CHLORINATED BRAKE CLEANER NON-VOC 15 OZ.	
WHMIS Classification	Class B Division 5 - Flammable Aerosol
Toluene (108-88-3)	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
Heptane, Branched Cyclic (426260	1-76-6)
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
Methanol (67-56-1)	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
Acetone (67-64-1)	
Listed on the Canadian DSL (Domes	tic Sustances List)
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects

# **EU-Regulations**

Toluene (108-88-3)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	

# Acetone (67-64-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)- Directive 79/831/EEC, sixth Amendment of Directive 67/548/EEC (dangerous substances)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

# Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Repr.Cat.3; R63

F; R11

T; R23/24/25

T; R39/23/24/25

Xn; R48/20

Xi; R36/38

Full text of R-phrases: see section 16

### 15.2.2. National regulations

05/12/2014 EN (English US) 11/13

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on KECI (Korean Existing Chemicals Inventory)

Listed on AICS (Australian Inventory of Chemical Substances)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on the Korean ECL (Existing Chemicals List)

# 15.3. US State regulations

FVP NON-CHLORINATED BRAKE CLEANER NON-VOC 15 OZ.		
State or local regulations	U.S California - Proposition 65 - Maximum Allowable Dose Levels (MADL)	

Acetone (67-64-1)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes				

# Toluene (108-88-3)

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

### Acetone (67-64-1)

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

Benzene 71-43-2

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

# **SECTION 16: Other information**

Other information : None.

Full text of H-phrases: see section 16:

ext of H-phrases: see section To:		
Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3	
Acute Tox. 3 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 3	
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3	
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1	
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1	
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3	
Asp. Tox. 1	Aspiration hazard Category 1	
Compressed gas	Gases under pressure Compressed gas	
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A	
Flam. Aerosol 2	Flammable aerosol Category 2	
Flam. Liq. 1	Flammable liquids Category 1	
Flam. Liq. 2	Flammable liquids Category 2	
Repr. 2	Reproductive toxicity Category 2	
Skin Irrit. 2	Skin corrosion/irritation Category 2	
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2	
STOT SE 1	Specific target organ toxicity (single exposure) Category 1	
STOT SE 3	Specific target organ toxicity (single exposure) Category 3	
H223	Flammable aerosol	
H224	Extremely flammable liquid and vapor	
H225	Highly flammable liquid and vapor	
H280	Contains gas under pressure; may explode if heated	
H301	Toxic if swallowed	
H304	May be fatal if swallowed and enters airways	
H311	Toxic in contact with skin	
H315	Causes skin irritation	
H319	Causes serious eye irritation	
H331	Toxic if inhaled	
H336	May cause drowsiness or dizziness	
H361	Suspected of damaging fertility or the unborn child	
H370	Causes damage to organs	

05/12/2014 EN (English US) 12/13

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

NFPA health hazard : 2 - Intense or continued exposure could cause temporary

incapacitation or possible residual injury unless prompt

medical attention is given.

NFPA fire hazard : 3 - Liquids and solids that can be ignited under almost all

ambient conditions.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



### **HMIS III Rating**

Personal Protection

Health : 2 Moderate Hazard - Temporary or minor injury may occur

: B

Flammability : 3 Serious Hazard
Physical : 1 Slight Hazard

SDS US (GHS HazCom 2012) - TCC

The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compiliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.

05/12/2014 EN (English US) 13/13