

SAFETY DATA SHEET

Issuing Date 29-Oct-2014 Revision Date 08-Mar-2017 Revision Number 2

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier

Product Name KOPR KOTE®

Other means of identification

Product Code(s) 100, 101

Synonyms MIL PRF-907F, NSN: 8030-00-251-3980

Recommended use of the chemical and restrictions on use

Recommended Use Lubricants, Greases and Release Products

Uses advised against No information available

Supplier's details

Manufacturer Address

Jet-Lube, LLC 930 Whitmore Dr. Rockwall, Texas 75087 TEL: 972-771-1000 Toll Free: 1-800-669-6318

Emergency telephone number

Emergency Telephone CHEMTREC: +1-703-527-3887 (INTERNATIONAL)

Number 1-800-424-9300 (NORTH AMERICA)

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200)

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2

GHS Label elements, including precautionary statements

Emergency Overview

Signal Word Warning Hazard Statements

Causes skin irritation

Causes serious eye irritation



Appearance Copper, Bronze

Physical State Semi-fluid (gel).

Odor Petroleum like

Precautionary Statements

Prevention

- · Wash face, hands and any exposed skin thoroughly after handling.
- Wear protective gloves/protective clothing/eye protection/face protection.

General Advice

• Specific treatment is urgent (see supplemental first aid instructions on this label)

Eves

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists: Get medical advice/attention.

Skin

- IF ON SKIN: Wash with plenty of soap and water.
- If skin irritation occurs: Get medical advice/attention.
- Take off contaminated clothing and wash before reuse.

Storage

None

Disposal

None

Hazard Not Otherwise Classified (HNOC)

Not applicable

Other information

20% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %	Trade secret
Lubricating greases A complex combination of hydrocarbons having carbon numbers predominantly in the range of C12 through C50. may contain organic salts of alkali metals, alkaline earth metals, etc.	74869-21-9	50-70	*
Graphite	7782-42-5	10-15	*
Copper	7440-50-8	8-13	*
Talc	14807-96-6	1-5	*
Limestone	1317-65-3	1-5	*
Molybdenum (IV) sulfide	1317-33-5	1-5	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of necessary first-aid measures

WPS-JLI-001US -KOPR KOTE® Revision Date . 08-Mar-2017

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If

symptoms persist, call a physician.

Skin Contact Wash off immediately with soap and plenty of water removing all contaminated clothes and

shoes. If skin irritation persists, call a physician.

Inhalation Move to fresh air. If symptoms persist, call a physician.

Ingestion Drink plenty of water. Do not induce vomiting without medical advice. Clean mouth with

water and afterwards drink plenty of water. If symptoms persist, call a physician.

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects No information available.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water spray. Carbon dioxide (CO₂). Foam. Dry powder. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

Specific Hazards Arising from the Chemical

Burning produces obnoxious and toxic fumes. Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). Heavy metal compounds

Explosion Data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Use personal protective equipment.

Environmental Precautions

Environmental Precautions Do not allow material to contaminate ground water system. Prevent product from entering

drains. See Section 12 for additional Ecological Information.

Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled

containers. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Wear personal protective equipment. Ensure adequate ventilation.

WPS-JLI-001US -KOPR KOTE[®] Revision Date . 08-Mar-2017

Conditions for safe storage, including any incompatibilities

Storage Keep container tightly closed in a dry and well-ventilated place. Keep in a bunded area

Incompatible Products Strong oxidizing agents. Acetylene. Vinyl compounds.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Graphite 7782-42-5	-	TWA: 15 mg/m³ total dust synthetic TWA: 5 mg/m³ total dust synthetic (vacated) TWA: 2.5 mg/m³ respirable dust natural (vacated) TWA: 10 mg/m³ total dust synthetic (vacated) TWA: 5 mg/m³ respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m ³ TWA: 2.5 mg/m ³ respirable dust
Copper 7440-50-8	TWA: 0.2 mg/m³ fume	TWA: 0.1 mg/m³ fume TWA: 1 mg/m³ dust and mist (vacated) TWA: 0.1 mg/m³ Cu dust, fume, mist	IDLH: 100 mg/m³ dust, fume and mist TWA: 1 mg/m³ dust and mist TWA: 0.1 mg/m³ fume
Talc 14807-96-6	TWA: 2 mg/m ³	(vacated) TWA: 2 mg/m ³	IDLH: 1000 mg/m³ containg no asbestos and <1% quartz TWA: 2 mg/m³
Limestone 1317-65-3	-	TWA: 15 mg/m³ TWA: 5 mg/m³ (vacated) TWA: 15 mg/m³ (vacated) TWA: 5 mg/m³	TWA: 5 mg/m³ respirable dust TWA: 10 mg/m³ total dust
Molybdenum (IV) sulfide 1317-33-5	TWA: 10 mg/m ³ Mo inhalable fraction TWA: 3 mg/m ³ Mo respirable fraction	TWA: 15 mg/m³ total dust (vacated) TWA: 10 mg/m³ Mo	IDLH: 5000 mg/m³ Mo

Immediately Dangerous to Life or Health. ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH:

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Measures Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection Skin and Body Protection Safety glasses with side-shields. Risk of contact, wear: Goggles.

Impervious clothing. Impervious gloves.

Respiratory ProtectionNone required under normal usage. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn.

experienced, 1410 of 1/14 approved respiratory protection should be worn.

Hygiene Measures When using, do not eat, drink or smoke. Remove and wash contaminated clothing before

re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Semi-fluid (gel)	Appearance	Copper Bronze
Odor	Petroleum like	Odor Threshold	No information available
<u>Property</u>	<u>Values</u>	Remarks/ - N	<u>Method</u>
pH	Neutral	None known	
Melting Point/Range	> 232 °C	None known	
Boiling Point/Boiling Range	< 316 °C	None known	
Flash Point	> 221 °C	None known	
Evaporation rate	<0.01	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limits in Air			
upper flammability limit	No data available		
lower flammability limit	No data available		
Vapor Pressure	<0.01 kPa @ 20°C	None known	
Vapor Density	>5 (air = 1)	None known	
Specific Gravity	1.15	None known	
Water Solubility	Insoluble in water.	None known	
Solubility in other solvents	Largely.	None known	
Partition coefficient: n-octane	ol/waterNo data available	None known	
Autoignition Temperature	> 260 °C / >500 °F	None known	
Decomposition Temperature	No data available	None known	
Viscosity	No data available	None known	
Flammable Properties	Not flammable		
Explosive Properties	No data available		
Oxidizing Properties	No data available		
Other information			
VOC Content (%)	None		
VOC (g/l)	None		

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Incompatible products.

Incompatible materials

Strong oxidizing agents. Acetylene. Vinyl compounds.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

WPS-JLI-001US -KOPR KOTE[®] Revision Date . 08-Mar-2017

Information on likely routes of exposure

Product Information

Inhalation None known.

Eye Contact Skin ContactCauses serious eye irritation.
Causes skin irritation.

Ingestion Not an expected route of exposure. May be harmful if swallowed. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhea.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Lubricating greases	= 2280 mg/kg (Rat)	-	-
A complex combination of hydrocarbons having carbon			
numbers predominantly in the range			
of C12 through C50. may contain			
organic salts of alkali metals, alkaline earth metals, etc.			

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects and also chronic effects from short and long term exposure

Sensitization No information available. **Mutagenic Effects** No information available.

Carcinogenicity Contains no ingredients above reportable quantities listed as a carcinogen.

Reproductive Toxicity
STOT - single exposure
STOT - repeated exposure
Aspiration Hazard

No information available.
No information available.
No information available.

Numerical measures of toxicity - Product

Acute Toxicity 20% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document:

LD50 Oral 2606 mg/kg; Acute toxicity estimate

12. ECOLOGICAL INFORMATION

Ecotoxicity

Aquatic toxicity is unlikely due to low solubility. Based on available data, the classification criteria are not met

Sea sediment LC50/10d/Corophium sp. = 925-3502 mg/kg

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Lubricating greases A complex combination of hydrocarbons having carbon numbers predominantly in the range of C12 through C50. may contain organic salts of alkali metals, alkaline earth metals, etc. 74869-21-9	>1001 mg/l	LC50 96 h: > 2000 mg/L (Salmo gairdneri)		

Copper	EC50 96 h: 0.031 - 0.054	LC50 96 h: 0.0068 - 0.0156		EC50 48 h: = 0.03 mg/L
·			_	
7440-50-8	mg/L static	mg/L (Pimephales		Static (Daphnia magna)
	(Pseudokirchneriella	promelas)		
	subcapitata)	LC50 96 h: < 0.3 mg/L static		
	EC50 72 h: 0.0426 - 0.0535	(Pimephales promelas) LC50		
	mg/L static	96 h: = 0.052 mg/L		
	(Pseudokirchneriella	flow-through (Oncorhynchus		
	` subcapitata)	mykiss)		
	, ,	LC50 96 h: = 0.112 mg/L		
		flow-through (Poecilia		
		reticulata)		
		LC50 96 h: = 0.2 mg/L		
		flow-through (Pimephales		
		promelas)		
		LC50 96 h: = 0.3 mg/L semi-		
		static (Cyprinus carpio) LC50		
		96 h: = 0.8 mg/L static		
		(Cyprinus carpio)		
		LC50 96 h: = 1.25 mg/L		
		static (Lepomis macrochirus)		
Talc		LC50 96 h: > 100 g/L		
14807-96-6		semi-static (Brachydanio		
		rerio)		

Persistence and Degradability No information available.

Bioaccumulation No information available.

Other Adverse Effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Dispose of in accordance with federal, state, and local regulations Where possible recycling

is preferred to disposal or incineration.

Contaminated Packaging Do not re-use empty containers.

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Copper	Toxic

14. TRANSPORT INFORMATION

DOT Not regulated

TDG Not regulated

MEX Not regulated

ICAO Not regulated

IATA Not regulated

IMDG/IMO Not regulated

RID Not regulated

ADN Not regulated

ADR Not regulated

15. REGULATORY INFORMATION

International Inventories

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Copper	7440-50-8	8-13	1.0

SARA 311/312 Hazard Categories

Acute Health HazardYesChronic Health HazardNoFire HazardNoSudden Release of Pressure HazardNoReactive HazardNo

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Copper		X	X	

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Copper	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

U.S. State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

"X" designates that the ingredients are listed on the state right to know list.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Graphite	Х	Х	Х		X
Copper	Х	Х	Х	Х	X
Talc	Х	X	X		X
Limestone	Х	Х	Х		X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WPS-JLI-001US -KOPR KOTE® Revision Date . 08-Mar-2017

16. OTHER INFORMATION

NFPA Health Hazard 2 Flammability 1 Instability 0 Physical and Chemical

Hazards -

Health Hazard 2 Flammability 1 Physical Hazard 0 Personal Protection X

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110 1-800-572-6501

Issuing Date 29-Oct-2014
Revision Date 08-Mar-2017

Revision Note Updated company information.

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet

