

Safety Data Sheet

Copyright, 2015, Meguiar's, Inc. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Meguiar's, Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 31-4420-1 **Version number:** 1.00 **Revision date:** 13/08/2015 **Supersedes date:** Initial issue.

Transportation version number: 1.00 (13/08/2015)

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

A1214, Cleaner Wax - Paste (22-143A): A1214

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Automotive.

1.3. Details of the supplier of the safety data sheet

Address: Meguiars United Kingdom Limited, 3 Lamport Court, Heartlands, Daventry, Northants, NN11 8UF

Telephone: +44 (0)870 241 6696 E Mail: info@meguiars.co.uk Website: www.meguiars.co.uk

1.4. Emergency telephone number

+44 (0)870 241 6696

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Flammable Solid, Category 1 - Flam. Sol. 1; H228 Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315 Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols:

GHS02 (Flame) |GHS07 (Exclamation mark) |

Pictograms





Ingredient CAS Nbr % by Wt Naphtha (petroleum), hydrotreated heavy 64742-48-9 30 - 60

HAZARD STATEMENTS:

H228 Flammable solid. H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

PRECAUTIONARY STATEMENTS

General:

P102 Keep out of reach of children.

Prevention:

P210A Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261A Avoid breathing vapours.

Response:

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P370 + P378G In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or

carbon dioxide to extinguish.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international

regulations.

12% of the mixture consists of components of unknown acute oral toxicity.

Contains 91% of components with unknown hazards to the aquatic environment.

Notes on labelling

Updated per Regulation (EC) No. 648/2004 on detergents. H304 is not required on the label due to the product's viscosity Ingredients required per 648/2004: >30%: Aliphatic hydrocarbons. Contains: Perfumes, benzyl benzoate. Nota P applied to CAS 64742-48-9.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EU Inventory	% by Wt	Classification
Naphtha (petroleum), hydrotreated heavy	64742-48-9	EINECS 265-	30 - 60	Asp. Tox. 1, H304 - Nota P

		150-3		(CLP) Skin Irrit. 2, H315; STOT SE 3, H336 (Self Classified)
Siloxanes and silicones, di-Me	63148-62-9		7 - 13	
Ceramic materials and wares, chemicals	66402-68-4	EINECS 266- 340-9	5 - 10	
Distillates (petroleum), hydrotreated light	64742-47-8	EINECS 265- 149-8	5 - 10	Asp. Tox. 1, H304 (CLP) Flam. Liq. 3, H226; STOT SE 3, H336; EUH066 (Self Classified)
Fatty acids, Montan-wax, Ethylene Esters	73138-45-1	EINECS 277- 291-8	7	
Kaolin, calcined	92704-41-1	EINECS 296- 473-8	1 - 5	
Conditioners	Trade Secret		< 5	
Glycerol poly(oxyethylene, oxypropylene) ether	9082-00-2		0.5 - 1.5	
Carnauba Wax	8015-86-9	EINECS 232- 399-4	1	
Stoddard solvent	8052-41-3	EINECS 232- 489-3	0 - 1	Asp. Tox. 1, H304; STOT RE 1, H372 - Nota P (CLP) Skin Irrit. 2, H315 (Self Classified)
Quartz	14808-60-7	EINECS 238- 878-4	< 0.2	STOT RE 1, H372 (Self Classified)

Please see section 16 for the full text of any H statements referred to in this section

Please refer to section 15 for any applicable Notas that have been applied to the above components

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eve contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

SubstanceConditionAldehydes.During combustion.FormaldehydeDuring combustion.Carbon monoxide.During combustion.Carbon dioxide.During combustion.Irritant vapours or gases.During combustion.Oxides of nitrogen.During combustion.

5.3. Advice for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (eg. gloves, respirators...) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient CAS Nbr Agency Limit type Additional comments

Quartz 14808-60-7 UK HSC TWA(respirable):0.1 mg/m3

Naphtha (petroleum), 64742-48-9 Manufacturer TWA:100 ppm

hydrotreated heavy determined

UK HSC: UK Health and Safety Commission

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended:

MaterialThickness (mm)Breakthrough TimeNeoprene.No data availableNo data available

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical stateSolid.Specific Physical Form:Paste

Appearance/Odour Sweet hydrocarbon odour; Light, cream-coloured paste

Odour thresholdNo data available.pHNot applicable.Boiling point/boiling range185 °C

Melting point

Not applicable.

Flammability (solid, gas) Flammable Solid: Category 1.

Explosive propertiesOxidising properties
Not classified
Not classified

Flash point 65.6 °C [Test Method:Pensky-Martens Closed Cup]

Autoignition temperatureNo data available.Flammable Limits(LEL)No data available.Flammable Limits(UEL)No data available.Vapour pressureNo data available.

Relative density 0.85 [*Ref Std*:WATER=1]

Water solubility Nil

Solubility- non-water
Partition coefficient: n-octanol/water
No data available.
Evaporation rate
No data available.
No data available.
No data available.
No data available.
Vapour density
No data available.
0.85 g/cm3

9.2. Other information

Volatile organic compounds (VOC) 44.97 % weight

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

Sparks and/or flames.

10.5 Incompatible materials

Strong acids. Strong bases.

Strong oxidising agents.

10.6 Hazardous decomposition products

Substance Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Naphtha (petroleum), hydrotreated heavy	Inhalation- Vapor		LC50 estimated to be 20 - 50 mg/l
Naphtha (petroleum), hydrotreated heavy	Dermal	Rabbit	LD50 > 3,000 mg/kg
Naphtha (petroleum), hydrotreated heavy	Ingestion	Rat	LD50 > 5,000 mg/kg
Siloxanes and silicones, di-Me	Dermal	Rabbit	LD50 > 19,400 mg/kg
Siloxanes and silicones, di-Me	Ingestion	Rat	LD50 > 17,000 mg/kg
Ceramic materials and wares, chemicals	Dermal		LD50 estimated to be > 5,000 mg/kg
Ceramic materials and wares, chemicals	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Distillates (petroleum), hydrotreated light	Dermal	Rabbit	LD50 > 3,160 mg/kg
Distillates (petroleum), hydrotreated light	Inhalation-	Rat	LC50 > 3 mg/l
	Dust/Mist		
	(4 hours)		

Dagger 7 of 16

Distillates (petroleum), hydrotreated light	Ingestion	Rat	LD50 > 5,000 mg/kg
Fatty acids, Montan-wax, Ethylene Esters	Ingestion	Rat	LD50 > 2,000 mg/kg
Kaolin, calcined	Ingestion	Rat	LD50 > 2,000 mg/kg
Glycerol poly(oxyethylene, oxypropylene) ether	Dermal	Rabbit	LD50 > 5,000 mg/kg
Glycerol poly(oxyethylene, oxypropylene) ether	Ingestion	Rat	LD50 > 10,000 mg/kg
Carnauba Wax	Dermal		LD50 estimated to be > 5,000 mg/kg
Carnauba Wax	Ingestion	Rat	LD50 > 8,800 mg/kg
Conditioners	Ingestion	Rat	LD50 > 2,500 mg/kg
Stoddard solvent	Inhalation-		LC50 estimated to be 20 - 50 mg/l
	Vapor		
Stoddard solvent	Dermal	Rabbit	LD50 > 3,000 mg/kg
Stoddard solvent	Ingestion	Rat	LD50 > 5,000 mg/kg
Quartz	Dermal		LD50 estimated to be > 5,000 mg/kg
Quartz	Ingestion		LD50 estimated to be > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Naphtha (petroleum), hydrotreated heavy	Rabbit	Irritant
Siloxanes and silicones, di-Me	Rabbit	No significant irritation
Ceramic materials and wares, chemicals	Rabbit	No significant irritation
Distillates (petroleum), hydrotreated light	Rabbit	Mild irritant
Carnauba Wax	Professio	No significant irritation
	nal	
	judgemen	
	t	
Conditioners	Professio	No significant irritation
	nal	
	judgemen	
	t	
Stoddard solvent	Rabbit	Irritant
Quartz	Professio	No significant irritation
	nal	
	judgemen	
	t	

Serious Eye Damage/Irritation

Name	Species	Value
Naphtha (petroleum), hydrotreated heavy	Rabbit	No significant irritation
Siloxanes and silicones, di-Me	Rabbit	No significant irritation
Ceramic materials and wares, chemicals	Rabbit	Mild irritant
Distillates (petroleum), hydrotreated light	Rabbit	Mild irritant
Carnauba Wax	Professio	No significant irritation
	nal	
	judgemen	
	t	
Conditioners	Professio	No significant irritation
	nal	
	judgemen	
	t	
Stoddard solvent	Rabbit	No significant irritation

Skin Sensitisation

Name	Species	Value
Naphtha (petroleum), hydrotreated heavy	Guinea	Not sensitising
	pig	
Distillates (petroleum), hydrotreated light	Guinea	Not sensitising
	pig	
Stoddard solvent	Guinea	Not sensitising
	pig	

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value		
Naphtha (petroleum), hydrotreated heavy	In vivo	Not mutagenic		
Naphtha (petroleum), hydrotreated heavy	In Vitro	Some positive data exist, but the data are not sufficient for classification		
Ceramic materials and wares, chemicals	In Vitro	Some positive data exist, but the data are not sufficient for classification		
Distillates (petroleum), hydrotreated light	In Vitro	Not mutagenic		
Stoddard solvent	In vivo	Not mutagenic		
Stoddard solvent	In Vitro	Some positive data exist, but the data are not sufficient for classification		
Quartz	In Vitro	Some positive data exist, but the data are not sufficient for classification		
Quartz	In vivo	Some positive data exist, but the data are not sufficient for classification		

Carcinogenicity

Name	Route	Species	Value
Naphtha (petroleum), hydrotreated heavy	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Naphtha (petroleum), hydrotreated heavy	Inhalation	Human and animal	Some positive data exist, but the data are not sufficient for classification
Ceramic materials and wares, chemicals	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Distillates (petroleum), hydrotreated light	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Stoddard solvent	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Stoddard solvent	Inhalation	Human and animal	Some positive data exist, but the data are not sufficient for classification
Quartz	Inhalation	Human and animal	Carcinogenic.

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Naphtha (petroleum), hydrotreated heavy	Inhalation	Not toxic to development	Rat	NOAEL 2.4 mg/l	during organogenesis
Stoddard solvent	Inhalation	Not toxic to development	Rat	NOAEL 2.4 mg/l	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure
						Duration
Naphtha (petroleum),	Inhalation	central nervous	May cause drowsiness or	Human	NOAEL Not	
hydrotreated heavy		system depression	dizziness	and	available	
				animal		
Naphtha (petroleum),	Inhalation	respiratory irritation	Some positive data exist, but the		NOAEL Not	
hydrotreated heavy			data are not sufficient for		available	
			classification			
Naphtha (petroleum),	Inhalation	nervous system	Some positive data exist, but the	Dog	NOAEL 6.5	4 hours

hydrotreated heavy			data are not sufficient for classification		mg/l	
Naphtha (petroleum), hydrotreated heavy	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	
Distillates (petroleum), hydrotreated light	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Distillates (petroleum), hydrotreated light	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Stoddard solvent	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Stoddard solvent	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Stoddard solvent	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 6.5 mg/l	4 hours
Stoddard solvent	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	me Route Target Organ(s) Value		Species	Test result	Exposure Duration	
Naphtha (petroleum), hydrotreated heavy	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 4.6 mg/l	6 months
Naphtha (petroleum), hydrotreated heavy	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 1.9 mg/l	13 weeks
Naphtha (petroleum), hydrotreated heavy	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL 0.6 mg/l	90 days
Naphtha (petroleum), hydrotreated heavy	Inhalation	bone, teeth, nails, and/or hair blood liver muscles	All data are negative	Rat	NOAEL 5.6 mg/l	12 weeks
Naphtha (petroleum), hydrotreated heavy	Inhalation	heart	All data are negative	Multiple animal species	NOAEL 1.3 mg/l	90 days
Ceramic materials and wares, chemicals	Inhalation	pulmonary fibrosis	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL not available	
Ceramic materials and wares, chemicals	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL not available	occupational exposure
Stoddard solvent	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 4.6 mg/l	6 months
Stoddard solvent	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 1.9 mg/l	13 weeks
Stoddard solvent	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL 0.6 mg/l	90 days
Stoddard solvent	Inhalation	bone, teeth, nails, and/or hair blood liver muscles	All data are negative	Rat	NOAEL 5.6 mg/l	12 weeks
Stoddard solvent	Inhalation	heart	All data are negative	Multiple animal species	NOAEL 1.3 mg/l	90 days
Quartz	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

Name	Value
Naphtha (petroleum), hydrotreated heavy	Aspiration hazard
Distillates (petroleum), hydrotreated light	Aspiration hazard
Stoddard solvent	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
Carnauba Wax	8015-86-9		Data not			
			available or			
			insufficient for			
			classification			
Ceramic	66402-68-4		Data not			
materials and			available or			
wares,			insufficient for			
chemicals			classification			
Fatty acids,	73138-45-1		Data not			
Montan-wax,			available or			
Ethylene Esters			insufficient for			
			classification			
Glycerol	9082-00-2	Inland	Estimated	96 hours	LC50	650 mg/l
poly(oxyethyle		Silverside				
ne,						
oxypropylene)						
ether						
Distillates	64742-47-8		Data not			
(petroleum),			available or			
hydrotreated			insufficient for			
light			classification			
Kaolin,	92704-41-1		Data not			
calcined			available or			
			insufficient for			
			classification			
Naphtha	64742-48-9		Data not			
(petroleum),			available or			
hydrotreated			insufficient for			
heavy			classification			
Conditioners	Trade Secret		Data not			
			available or			
			insufficient for			
			classification			

Siloxanes and silicones, di- Me	63148-62-9	Data not available or insufficient for classification	
Quartz	14808-60-7	Data not available or insufficient for classification	
Stoddard solvent	8052-41-3	Data not available or insufficient for classification	

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Ceramic materials and wares, chemicals	66402-68-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Fatty acids, Montan-wax, Ethylene Esters	73138-45-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Distillates (petroleum), hydrotreated light	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Siloxanes and silicones, di- Me	63148-62-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Glycerol poly(oxyethyle ne, oxypropylene) ether	9082-00-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Quartz	14808-60-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Conditioners	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Kaolin, calcined	92704-41-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Carnauba Wax	8015-86-9	Modeled Biodegradation	28 days	BOD	82 % weight	OECD 301F - Manometric

Page: 12 of 15

						respirometry
Stoddard	8052-41-3	Experimental	28 days	CO2 evolution	63 % weight	OECD 301B - Modified
solvent		Biodegradation				sturm or CO2
Stoddard	8052-41-3	Estimated		Photolytic half-	6.49 days (t	Other methods
solvent		Photolysis		life (in air)	1/2)	

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Distillates (petroleum), hydrotreated light	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Kaolin, calcined	92704-41-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Glycerol poly(oxyethyle ne, oxypropylene) ether	9082-00-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Siloxanes and silicones, di- Me	63148-62-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Conditioners	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Fatty acids, Montan-wax, Ethylene Esters	73138-45-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Ceramic materials and wares, chemicals	66402-68-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Quartz	14808-60-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
	8015-86-9	Modeled Bioaccumulatio n		Log Kow	23.45	Other methods
Stoddard solvent	8052-41-3	Experimental Bioconcentrati on		Log Kow	7.06	Other methods
Stoddard solvent	8052-41-3	Experimental BCF - Other		Bioaccumulatio n factor		Other methods
Fatty acids,	73138-45-1	Estimated		Bioaccumulatio	20.5	Other methods

Page: 13 of 15

Montan-wax,	Bioconcentrati	n factor	
Ethylene Esters	on		

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

No information available at this time, contact manufacturer for more details

12.6. Other adverse effects

No information available.

The surfactant(s) contained in this preparation comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

See Section 11.1 Information on toxicological effects

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of the manufacturer, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/CE and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor

EU waste code (product as sold)

070604* Other organic solvents, washing liquids and mother liquors

SECTION 14: Transportation information

ADR/IMDG/IATA: Not restricted for transport.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

IngredientCAS NbrClassificationRegulationQuartz14808-60-7Grp. 1: Carcinogenic to humansInternational Agency for Research on Cancer

Global inventory status

Contact manufacturer for more information The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements

of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA.

15.2. Chemical Safety Assessment

Not applicable

SECTION 16: Other information

List of relevant H statements

EUH066 Repeated exposure may cause skin dryness or cracking.

H226 Flammable liquid and vapour.

H228 Flammable solid.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

Revision information:

No revision information

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Meguiar's, Inc. United Kingdom MSDSs are available at www.meguiars.co.uk