

Material Safety Data Sheet

FIR No.:	187175		Level:	2
Version Number:	US-US-4		Release Date:	2015-02-02
1. Product and Compa	any Identificati	on		
Product Name:		Orange Antifreeze/Coolant Prediluted		
Product Code:		See Attachment		
Application:		Engine Antifreeze/Coolant		
Supplier:		Ford Motor Company Attention: MSDS Information, P.O. Box 1899 Dearborn, Michigan 48121 1-800-392-3673		
Emergency Telephor	ne:	Poison Control Center: 1-800-959-3673 CHEMTREC: U.S. and Canada: 1-800-424-930 CHEMTREC: International: 1-703-527-3887	00	

2. Composition/Information on Ingredients

This chemical product is a preparation.

Chemical Name	CAS Number	Percent Concentration	Hazard Classification
ETHYLENE GLYCOL	107-21-1	30-60	ACGIH/OSHA CAA-HAP DSL LISTED HAZCOM WHMIS 1 PEL/TLV-US RQ RSMS_D_ALL SARA 313 LOCAL REV 1
3. Hazards Identification WARNING			

Health:	Harmful or fatal if swallowed. Aspiration hazard if swallowed; can enter lungs and cause damage. May cause skin and eye irritation. Inhalation of mist and vapors may irritate the nose, throat, and lungs. Excessive inhalation of this material causes headache, dizziness, nausea and incoordination. Overexposure may affect kidneys and nervous system.
Environment:	Material contains a chemical which is a Hazardous Air Pollutant (HAP), regulated by the United States Clean Air Act.



FIR No.:	187175	Level: 2
Version Number:	US-US-4	Release Date: 2015-02-02
4. First-Aid Measures		
Inhalation:		If gas/fume/vapor/dust/mist from the material is inhaled, remove the affected person immediately to fresh air. If irritation persists, get medical attention.
Skin Contact:		Immediately take off all contaminated clothing. For skin contact flush with large amounts of water. Wash skin with soap and water. If irritation persists, get medical attention.
Eye Contact:		In case of contact with eyes, rinse immediately with plenty of water for at least 15 minutes and seek medical attention. If irritation persists, get medical attention.
Ingestion:		If the material is swallowed, do not induce vomiting. Get immediate medical attention or advice give several glasses of water or milk. Do not give anything by mouth to an unconscious or convulsing person.
Most Important Symp	otoms Effects:	Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.
Notes to a Physician:		If the affected person is not breathing, apply artificial respiration. This material, if aspirated into the lungs, may cause chemical pneumonitis; treat the affected person appropriately.
5. Fire-Fighting Measu	ires	
Extinguishing Media:		Dry chemical, foam, carbon dioxide, water fog.
Specific Methods:		Use water to cool fire-exposed containers, structures, and to protect personnel. Use water to dilute spills and to disperse flammable vapors.
Specific Hazards:		Vapors emitted may form a flammable mixture with air. Irritating and/or toxic fumes and gases may be emitted upon the product's decomposition. Empty containers may retain product residue including Flammable or Explosive vapors. Do not cut, drill, grind, or weld near full, partially full, or empty product containers.
Protection of Firefigh	ters:	Fire fighters should be equipped with NIOSH-approved, self-contained breathing apparatus (SCBA) and full protective clothing.
6. Accidental Release	Measures	
Personal Precautions	:	Avoid inhalation of vapors and contact with skin and eyes. Surfaces may become slippery after spillage. Wear appropriate protective equipment and clothing during clean-up.



FIR No.:		187175		Level:	2
Version Nur	nber:	US-US-4		Release Date:	2015-02-02
Environm	nental Precau	tions:	open water cour	spilled product to enter public drainage s ses. material to drain into sewers/water supp	-
Methods for Cleaning Up:		Contain the disc Absorb the spille material.	harged material. d material with an inert absorbent (nonfla	ammable)	
7. Handling	and Storage	9			
Handling	:				
	Technical M	easures:	handled at low te ventilation is nee	nical) room ventilation is expected to be s imperatures or in covered equipment. Lo ded in the presence of airborne mists. t from heat, sparks, or open flame.	
	Precautions Handling:	and Advice for Safe	Elevated tempera fumes which may Avoid breathing	er closed when not in use.	ors, mist, or
Storage:	Technical M	easures:	Do not allow the	product to freeze.	
	Storage Cor	nditions:	Keep the contain	material in open or unlabeled containers er tightly closed and in a cool, well-ventil t away from strong oxidizing agents.	
8. Exposur	e Controls/P	Personal Protection	1		
Enginee	ering Measure	es:	exposure limits/g and/or mist, use engineering cont	ntilation to control airborne concentration uidelines. If user operations generate a v process enclosure, local exhaust ventilat rols to control airborne levels below the cosure limits/guidelines.	apor, dust,
=	sure Limits: lical Name		STEL/C	References	
ETHY	LENE GLYCC)L	C 100(mg/m3)	ACGIH	



FIR No.:	187175	Level: 2		
Version Number:	US-US-4	Release Date: 2015-02-02		
Personal Protective Equ	uipment:			
Respiratory Protection:		If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with the requirements of OSHA Respiratory Protection Standard 29 CFR 1910.134 and/or Canadian Standard CSA Z94.4.		
Hand Protection:		The use of neoprene gloves is recommended. The use of nitrile gloves is recommended. The use of polyvinyl chloride gloves is recommended.		
Eye Protection:		Wear safety glasses with side shields. Wear chemical goggles; face shield (if splashing is possible).		
Skin and Body Protection	on:	Remove contaminated clothing and wash before reuse.		
Hygiene Measures:		When using this material, do not eat, drink or smoke. Use good personal hygiene.		

Ford Motor Company,

FIR No.:	187175	Level: 2
Version Number:	US-US-4	Release Date: 2015-02-02
9. Physical and Chemi	cal Properties	
Specific Gravity:		1.1 H2O=1 @15°C
Physical State:		FLUID
Form:		LIQUID
Odor:		CHARACTERISTIC
Color:		ORANGE
рН:		N.AP
Temperature Range Du in Physical State Occur		
Boiling I	Point:	>100 °C
Freezing	g Point:	-30 °C
Melting	Point:	N.AP
Flash Point:		130 °C PMCC
Auto-ignition Temperat	ure:	>200 °C
Explosion Properties:		
UEL:		15 %(V)
LEL:		3 %(V)
Vapor Pressure:		N.AV
Vapor Density:		N.AV
Solubility:		COMPLETE IN WATER
Viscosity:		30 cSt @40°C
Evaporation Rate:		N.AV
10. Stability and React	ivity	
Stability:		This is a stable material. Hazardous polymerization will not occur.
Conditions and Materia	ls to Avoid:	This product may react with strong oxidizing agents (bleachsodium hypochlorite, calcium hypochlorite, hydrogen peroxide, permanganate, nitric acid, concentrated OXYGEN, perchlorates).
Hazardous Decomposit	ion Products:	Carbon monoxide, carbon dioxide, and other low molecular weight hydrocarbons. Irritating and/or toxic gases may be emitted upon the product's decomposition.



FIR No.:	187175	Level:	2
	US-US-4	Release Date:	
Version Number:		Release Date:	2015-02-02
11. Toxicological Info			
	YLENE GLYCOL it, LD50 = 9530 mg/kg		
107-21-1 ETH			
Oral, adult rat, L	.D50 = 4700 mg/kg		
hale a la Carra		Evenenues to all mist/fume/vaner may aquee reepiratery to	a at irritation
Inhalation:		Exposure to oil mist/fume/vapor may cause respiratory tra Intentional misuse by deliberately concentrating and inha	
		contents may be harmful or fatal.	5
	· · · · · · · · · · · · · · · · · · ·	Ethylene alweet has been fototoxic and torotogonic in rate and miss	
Chronic (Long Term) Toxicity:		Ethylene glycol has been fetotoxic and teratogenic in rats and mice, which has been confirmed by independent studies. The actual	
		reproductive hazard of ethylene glycol in humans is unkn	
12. Ecological Informa	ation		
No specific aquatic	data available for this pro	duct.	
13. Disposal Consider	rations		
Waste from Residues:		Dispose of waste material according to Local, State, Fed	eral, and
		Provincial Environmental Regulation. Empty containers may contain hazardous residues (vapo	rs liquid
		and/or solid). Do not reuse the empty container without c	
		cleaning or reconditioning.	
Contaminated Packagi	na.	No consideration given when disposed of according to lo	cal state and
oontaniniateu i ackayi		Federal regulations.	



(Stind) 🗄 LINCOLN 🕡 Mercury Motorcraft Rotunda

Material Safety Data Sheet

FIR No.:	187175
Version Number:	US-US-4

Level: 2 Release Date: 2015-02-02

14. Transport Information

U.S. Department of Transportation (DOT) 49 - CFR 172.101 This product is not regulated as a dangerous good.

Canadian Transportation of Dangerous Goods (T.D.G.) - TDGR Schedule II

This product is not regulated as a dangerous good.

Secretary of Communication and Transportation (SCT) - NOM-002-SCT2/1994 (Mexico) This product is not regulated as a dangerous good.

International and Domestic Air Transportation - ICAO & IATA Section 4.2

This product is not regulated as a dangerous good.

International Water Transportation - IMDG Code Amendment 31-02

This product is not regulated as a dangerous good.

15. Regulatory Information

The components of this product are listed on the TSCA Inventory This product contains a toxic chemical or chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372. This product contains an ingredient(s) considered to be a hazardous substance by the State of Pennsylvania (Pennsylvania Worker and Community Right to Know Act). This product contains an ingredients(s) considered to be a hazardous substance(s) by the State of New Jersey.

16. Other Information

Key/Legend: N.AP = Not applicable; N.AV = Not available; ND = Not determined or No data; TLV = Threshold limit value; TWA = Time-weighted average; STEL = Short-term exposure limit; C = Ceiling limit

HMIS and NFPA Hazard Class Information:

HMIS Hazard Class:	Health: 2 (Moderate)	Flammability: 1 (Slight)	Physical Hazard: 0 (Least)
NFPA Hazard Class:	Health: 2 (Moderate)	Flammability: 1 (Slight)	Instability: 0 (Least)

Preparation Information:

The chemical identification and properties for this material were provided by the manufacturer. Health and safety information has been evaluated by the Occupational and Environmental Health Sciences Department, Ford Motor Company, Diagnostic Service Center II, 1800 Fairlane Drive, Allen Park, MI 48101, USA.



FIR No.:	187175	Level: 2
Version Number:	US-US-4	Release Date: 2015-02-02
Disclaimer:		The information on this data sheet represents our current data and is accurate to the best of our knowledge as to the proper handling of this product under normal conditions and in accordance with the application specified on the packaging and/or technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.



FIR No.: Version Number:	187175 US-US-4		Level: 2 Release Date: 2015-02-02
	Δ	ttachment	
Product Code	Container Size	Part of Kit	Kit Product Code
VC-3DIL-B	1 U.S. gal.		
VC-3DIL-B1	1 U.S. gal.		
VC-3DIL-BD	55 U.S. gal.		