

FIR No.: 187174 Level: 2

Version Number: US-US-3 Release Date: 2014-05-12

1. Product and Company Identification

Product Name: Orange Antifreeze/Coolant Concentrated

Product Code: See Attachment

Application:Engine Antifreeze/CoolantSupplier:Ford Motor Company

Attention: MSDS Information, P.O. Box 1899

Dearborn, Michigan 48121

1-800-392-3673

Emergency Telephone: Poison Control Center: 1-800-959-3673

CHEMTREC: U.S. and Canada: 1-800-424-9300 CHEMTREC: International: 1-703-527-3887

2. Composition/Information on Ingredients

This chemical product is a preparation.

Chemical Name CAS Number Percent Hazard

Concentration Classification

ETHYLENE GLYCOL 107-21-1 60-100 ACGIH/OSHA

CAA-HAP
DSL LISTED
HAZCOM
WHMIS 1
PEL/TLV-US

RQ

RSMS_D_ALL SARA 313 LOCAL REV 1

3. Hazards Identification

WARNING

Health: Harmful or fatal if swallowed.

Aspiration hazard if swallowed; can enter lungs and cause damage.

May cause skin and eye irritation.

Inhalation of mist and vapors may irritate the nose, throat, and lungs. Excessive inhalation of this material causes headache, dizziness,

nausea and incoordination.

Overexposure may affect kidneys and nervous system.

Environment: Material contains a chemical which is a Hazardous Air Pollutant (HAP),

regulated by the United States Clean Air Act.

Owner: Ford Motor Company PRINTED DOCUMENT IS TRANSIENT Ford Proprietary

Application: MATS Page: 1 / 9 Official Record



FIR No.: 187174 Level: 2

Version Number: US-US-3 Release Date: 2014-05-12

4. First-Aid Measures

Inhalation: If gas/fume/vapor/dust/mist from the material is inhaled, remove the

affected person immediately to fresh air. If irritation persists, get medical attention.

Skin Contact: Immediately take off all contaminated clothing.

For skin contact flush with large amounts of water.

Wash skin with soap and water.

If irritation persists, get medical attention.

Eye Contact: In case of contact with eyes, rinse immediately with plenty of water for

at least 15 minutes and seek medical attention. If irritation persists, get medical attention.

Ingestion: If the material is swallowed, do not induce vomiting. Get immediate

medical attention or advice -- give several glasses of water or milk. Do not give anything by mouth to an unconscious or convulsing person.

Most Important Symptoms Effects: Headache, dizziness, nausea, and loss of coordination are indications

of excessive exposure to vapors or spray mists.

Notes to a Physician: If the affected person is not breathing, apply artificial respiration.

This material, if aspirated into the lungs, may cause chemical

pneumonitis; treat the affected person appropriately.

5. Fire-Fighting Measures

Extinguishing Media: Dry chemical, foam, carbon dioxide, water fog.

Specific Methods:Use water to cool fire-exposed containers, structures, and to protect

personnel.

Use water to dilute spills and to disperse flammable vapors.

Specific Hazards: Vapors emitted may form a flammable mixture with air.

Irritating and/or toxic fumes and gases may be emitted upon the

product's decomposition.

Empty containers may retain product residue including Flammable or Explosive vapors. Do not cut, drill, grind, or weld near full, partially full,

or empty product containers.

Protection of Firefighters: Fire fighters should be equipped with NIOSH-approved, self-contained

breathing apparatus (SCBA) and full protective clothing.

6. Accidental Release Measures

Personal Precautions: Avoid inhalation of vapors and contact with skin and eyes.

Surfaces may become slippery after spillage.

Wear appropriate protective equipment and clothing during clean-up.

Owner: Ford Motor Company PRINTED DOCUMENT IS TRANSIENT Ford Proprietary

Application: MATS Page: 2 / 9 Official Record



FIR No.: 187174 Level: 2

Version Number: US-US-3 Release Date: 2014-05-12

Environmental Precautions:Do not allow the spilled product to enter public drainage system or

open water courses.

Do not allow this material to drain into sewers/water supplies.

Methods for Cleaning Up: Contain the discharged material.

Absorb the spilled material with an inert absorbent (nonflammable)

material.

7. Handling and Storage

Handling:

Technical Measures: General (mechanical) room ventilation is expected to be satisfactory if

handled at low temperatures or in covered equipment. Local ventilation is needed in the presence of airborne mists. Keep this product from heat, sparks, or open flame.

Precautions and Advice for Safe

Handling:

Do not get this material in your eyes, on your skin, or on your clothing.

Elevated temperature or mechanical action may form vapors, mist, or fumes which may be irritating to the eyes, nose, throat, and lungs.

Avoid breathing vapors or mist.

Keep the container closed when not in use.

Use with adequate ventilation.

Storage: Technical Measures: Do not allow the product to freeze.

Storage Conditions: Do not store this material in open or unlabeled containers.

Keep the container tightly closed and in a cool, well-ventilated place.

Store this product away from strong oxidizing agents.

8. Exposure Controls/Personal Protection

Engineering Measures: Use adequate ventilation to control airborne concentrations below the

exposure limits/guidelines. If user operations generate a vapor, dust, and/or mist, use process enclosure, local exhaust ventilation, or other

engineering controls to control airborne levels below the

recommended exposure limits/guidelines.

Exposure Limits:

Chemical Name STEL/C References

ETHYLENE GLYCOL C 100(mg/m3) ACGIH

Owner: Ford Motor Company PRINTED DOCUMENT IS TRANSIENT Ford Proprietary

Application: MATS Page: 3 / 9 Official Record



FIR No.: 187174 Level: 2

Version Number: US-US-3 Release Date: 2014-05-12

Personal Protective Equipment:

Respiratory Protection: If engineering controls do not maintain airborne concentrations to a

level which is adequate to protect worker health, an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with the requirements of OSHA Respiratory Protection Standard 29 CFR 1910.134 and/or Canadian Standard

CSA Z94.4.

Hand Protection: The use of neoprene gloves is recommended.

The use of nitrile gloves is recommended.

The use of polyvinyl chloride gloves is recommended.

Eye Protection: Wear safety glasses with side shields.

Wear chemical goggles; face shield (if splashing is possible).

Skin and Body Protection: Remove contaminated clothing and wash before reuse.

Hygiene Measures: When using this material, do not eat, drink or smoke.

Use good personal hygiene.

Owner: Ford Motor Company PRINTED DOCUMENT IS TRANSIENT Ford Proprietary
Application: MATS Page: 4 / 9 Official Record



FIR No.: 187174 Level: 2

Version Number: US-US-3 Release Date: 2014-05-12

9. Physical and Chemical Properties

Specific Gravity: 1.1 @15°C

Physical State: LIQUID

Form: LIQUID

Odor: CHARACTERISTIC

Color: ORANGE

pH: N.AP

Temperature Range During which Changes

in Physical State Occur:

Boiling Point:

Freezing Point:

Melting Point:

N.AP

Flash Point: 130 °C PMCC

Auto-ignition Temperature: >200 °C

Explosion Properties:

 UEL:
 15 %(V)

 LEL:
 3 %(V)

 Vapor Pressure:
 N.AV

 Vapor Density:
 N.AV

Solubility: COMPLETE IN WATER

Viscosity: 30 cSt @40°C

Evaporation Rate: N.AV

10. Stability and Reactivity

Stability: This is a stable material.

Hazardous polymerization will not occur.

Conditions and Materials to Avoid: This product may react with strong oxidizing agents (bleach--sodium

hypochlorite, calcium hypochlorite, hydrogen peroxide, permanganate,

nitric acid, concentrated OXYGEN, perchlorates).

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, and other low molecular weight

hydrocarbons.

Irritating and/or toxic gases may be emitted upon the product's

decomposition.

Owner: Ford Motor Company PRINTED DOCUMENT IS TRANSIENT Ford Proprietary
Application: MATS Page: 5 / 9 Official Record



FIR No.: 187174 Level: 2

Version Number: US-US-3 Release Date: 2014-05-12

11. Toxicological Information

107-21-1 ETHYLENE GLYCOL Skin, adult rabbit, LD50 = 9530 mg/kg 107-21-1 ETHYLENE GLYCOL Oral, adult rat, LD50 = 4700 mg/kg

Inhalation: Exposure to oil mist/fume/vapor may cause respiratory tract irritation.

Intentional misuse by deliberately concentrating and inhaling the

contents may be harmful or fatal.

Chronic (Long Term) Toxicity: Ethylene glycol has been fetotoxic and teratogenic in rats and mice,

which has been confirmed by independent studies. The actual reproductive hazard of ethylene glycol in humans is unknown.

12. Ecological Information

No specific aquatic data available for this product.

13. Disposal Considerations

Waste from Residues: Dispose of waste material according to Local, State, Federal, and

Provincial Environmental Regulation.

Empty containers may contain hazardous residues (vapors, liquid, and/or solid). Do not reuse the empty container without commercial

cleaning or reconditioning.

Contaminated Packaging: No consideration given when disposed of according to local, state, and

Federal regulations.

Owner: Ford Motor Company PRINTED DOCUMENT IS TRANSIENT Ford Proprietary

Application: MATS Page: 6 / 9 Official Record



FIR No.: 187174 Level: 2

Version Number: US-US-3 Release Date: 2014-05-12

14. Transport Information

U.S. Department of Transportation (DOT) 49 - CFR 172.101

This product is not regulated as a dangerous good.

Canadian Transportation of Dangerous Goods (T.D.G.) - TDGR Schedule II

This product is not regulated as a dangerous good.

Secretary of Communication and Transportation (SCT) - NOM-002-SCT2/1994 (Mexico)

This product is not regulated as a dangerous good.

International and Domestic Air Transportation - ICAO & IATA Section 4.2

This product is not regulated as a dangerous good.

International Water Transportation - IMDG Code Amendment 31-02

This product is not regulated as a dangerous good.

15. Regulatory Information

The components of this product are listed on the TSCA Inventory

This product contains a toxic chemical or chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

This product contains an ingredient(s) considered to be a hazardous substance by the State of Pennsylvania (Pennsylvania Worker and Community Right to Know Act).

This product contains an ingredients(s) considered to be a hazardous substance(s) by the State of New Jersey.

16. Other Information

Key/Legend: N.AP = Not applicable; N.AV = Not available; ND = Not determined or No data; TLV = Threshold limit value; TWA = Time-weighted average; STEL = Short-term exposure limit; C = Ceiling limit

HMIS and NFPA Hazard Class Information:

HMIS Hazard Class: Health: 2 (Moderate) Flammability: 1 (Slight) Physical Hazard: 0 (Least)

NFPA Hazard Class: Health: 2 (Moderate) Flammability: 1 (Slight) Instability: 0 (Least)

Preparation Information: The chemical identification and properties for this material were provided

by the manufacturer. Health and safety information has been evaluated by the Occupational and Environmental Health Sciences Department, Ford Motor Company, Diagnostic Service Center II, 1800 Fairlane Drive,

Allen Park, MI 48101, USA.

Owner: Ford Motor Company PRINTED DOCUMENT IS TRANSIENT Ford Proprietary

Application: MATS Page: 7 / 9 Official Record







Motorcraft

Rotunda

Material Safety Data Sheet

FIR No.: 187174 Level: 2

Version Number: US-US-3 Release Date: 2014-05-12

Disclaimer:

The information on this data sheet represents our current data and is accurate to the best of our knowledge as to the proper handling of this product under normal conditions and in accordance with the application specified on the packaging and/or technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.

Owner: Ford Motor Company PRINTED DOCUMENT IS TRANSIENT Ford Proprietary
Application: MATS Page: 8 / 9 Official Record







Rotunda

Level: 2

Material Safety Data Sheet

187174 FIR No.:

Release Date: 2014-05-12 US-US-3 **Version Number:**

Attachment

Part of Kit **Product Code Container Size Kit Product Code**

VC-3-B 1 U.S. gal. VC-3-B1 1 U.S. gal.

Owner: Ford Motor Company Application: MATS

PRINTED DOCUMENT IS TRANSIENT

Ford Proprietary Official Record