

**SAFETY-KLEEN PREMIUM SOLVENT  
SAFETY-KLEEN PREMIUM GOLD SOLVENT  
(VIRGIN AND RECYCLED)  
MATERIAL SAFETY DATA SHEET FOR USA AND CANADA**



**SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

**PRODUCT NAME:** SAFETY-KLEEN PREMIUM SOLVENT  
SAFETY-KLEEN PREMIUM GOLD SOLVENT  
(VIRGIN AND RECYCLED)

**SYNONYMS:** Parts Washer Solvent; Petroleum Distillates; Petroleum Naphtha;  
Naphtha, Solvent; Stoddard Solvent; Mineral Spirits.

**PRODUCT CODE:** 6605, 6616

**PRODUCT USE:** Cleaning and degreasing metal parts.  
If this product is used in combination with other products, refer to the  
Material Safety Data Sheet for those products.

These numbers are for  
emergency use only. If  
you desire non-emergency  
product information,  
please call a phone  
number listed below.

**24-HOUR EMERGENCY PHONE NUMBER  
MEDICAL AND TRANSPORTATION (SPILL):**

**1-800-468-1760**

**SUPPLIER:** Safety-Kleen Systems, Inc.  
5360 Legacy Drive  
Building 2, Suite 100  
Plano, Texas 75024  
USA  
**1-800-669-5740**  
**www.Safety-Kleen.com**

**TECHNICAL INFORMATION:** 1-800-669-5740 Press 1 then Enter 7500

**MSDS FORM NUMBER:** 82658

**ISSUE:** November 30, 2009

**ORIGINAL ISSUE:** January 26, 1995

**SUPERSEDES:** August 21, 2009

**PREPARED BY:** Product MSDS Coordinator

**APPROVED BY:** MSDS Task Force

**SAFETY-KLEEN PREMIUM SOLVENT**  
**SAFETY-KLEEN PREMIUM GOLD SOLVENT (VIRGIN AND RECYCLED)**  
**MATERIAL SAFETY DATA SHEET FOR USA AND CANADA**

**SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS**

WT%	NAME	SYNONYM	CAS NO.	TWA	OSHA PEL**	ACGIH TLV®		LD <sup>a</sup>	LC <sup>b</sup>
					STEL ppm	TWA ppm	STEL		
100	Distillates (petroleum), hydrotreated light	N. Av.	64742-47-8	500 <sup>c</sup> ppm 2900 <sup>c</sup> mg/m <sup>3</sup>	N. Av.	100 <sup>c</sup>	N. Av.	5000 <sup>c</sup> mg/kg	5500 <sup>c</sup> mg/m3/4h

\*\*OSHA Final PEL value (enforceable). Some States have adopted more stringent values.

N. Av. = Not Available

<sup>b</sup>Inhalation-Rat LC<sub>50</sub>

<sup>c</sup>Based on Stoddard Solvent

<sup>a</sup>Oral-Rat LD<sub>50</sub>

**SECTION 3: HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW**

**APPEARANCE**

Liquid, clear, colorless to pale yellow, mild hydrocarbon odor.

**WARNING!**

**PHYSICAL HAZARDS**

Combustible liquid and vapor.

**HEALTH HAZARDS**

May be harmful if inhaled.

May irritate the respiratory tract (nose, throat, and lungs), eyes, and skin.

May be harmful if swallowed.

Contains material that may cause central nervous system and kidney damage.

**ENVIRONMENTAL HAZARDS**

Not toxic to aquatic life.

**SAFETY-KLEEN PREMIUM SOLVENT**  
**SAFETY-KLEEN PREMIUM GOLD SOLVENT (VIRGIN AND RECYCLED)**  
**MATERIAL SAFETY DATA SHEET FOR USA AND CANADA**

---

**POTENTIAL HEALTH EFFECTS**

**INHALATION (BREATHING):** High concentrations of vapor may be harmful if inhaled. High concentrations of vapor or mist may irritate the respiratory tract (nose, throat, and lungs). High concentrations of vapor or mist may cause nausea, vomiting, headaches, dizziness, loss of coordination, numbness, and other central nervous system effects. Massive acute overexposure may cause rapid central nervous system depression, sudden collapse, coma, and/or death.

**EYES:** May cause irritation.

**SKIN:** May cause irritation. Not likely to be absorbed in harmful amounts.

**INGESTION (SWALLOWING):** May be harmful if swallowed. May cause throat irritation, nausea, vomiting, and central nervous system effects as noted under **INHALATION (BREATHING)**. Breathing product into the lungs during ingestion or vomiting may cause lung injury and possible death.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** Individuals with pre-existing respiratory tract (nose, throat, and lungs), central nervous system, kidney, eye, and/or skin disorders may have increased susceptibility to the effects of exposure.

**CHRONIC:** Prolonged or repeated inhalation may cause toxic effects as noted under **INHALATION (BREATHING)**. Prolonged or repeated exposure may cause central nervous system and kidney damage. Prolonged or repeated eye contact may cause inflammation of the membrane lining the eyelids and covering the eyeball (conjunctivitis). Prolonged or repeated skin contact may cause drying, cracking, redness, itching, swelling (dermatitis) and/or burns..

**CANCER INFORMATION:** No known carcinogenicity. For more information, see **SECTION 11: CARCINOGENICITY**.

Also see **SECTION 15: CALIFORNIA**.

**POTENTIAL ENVIRONMENTAL EFFECTS**

Product is not toxic to aquatic life. Also see **SECTION 12: ECOLOGICAL INFORMATION**.

<b>SECTION 4: FIRST AID MEASURES</b>
--------------------------------------

**INHALATION (BREATHING):** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Oxygen should only be administered by qualified personnel. Someone should stay with victim. Get medical attention if breathing difficulty persists.

**SAFETY-KLEEN PREMIUM SOLVENT**  
**SAFETY-KLEEN PREMIUM GOLD SOLVENT (VIRGIN AND RECYCLED)**  
**MATERIAL SAFETY DATA SHEET FOR USA AND CANADA**

---

**EYES:** If irritation or redness from exposure to vapor develops, move away from exposure into fresh air. Upon contact, immediately flush eyes with plenty of lukewarm water, holding eyelids apart, for 15 minutes. Get medical attention.

**SKIN:** Remove affected clothing and shoes. Wash skin thoroughly with soap and water. Get medical attention if irritation or pain develops or persists.

**INGESTION (SWALLOWING):** Do NOT induce vomiting. Immediately get medical attention. Call 1-800-468-1760 for additional information. If spontaneous vomiting occurs, keep head below hips to avoid breathing the product into the lungs. Never give anything by mouth to an unconscious person.

**NOTE TO PHYSICIANS:** Treat symptomatically and supportively. Treatment may vary with condition of victim and specifics of incident. Call 1-800-468-1760 for additional information.

<b>SECTION 5: FIRE FIGHTING MEASURES</b>
--

<b>FLASH POINT:</b>	148°F (64°C) (approximately) Tag Closed Cup
<b>FLAMMABLE LIMITS IN AIR:</b>	<b>LOWER:</b> 0.7 VOL% (minimum) <b>UPPER:</b> 5 VOL% (maximum)
<b>AUTOIGNITION TEMPERATURE:</b>	480°F (249°C) (minimum)
<b>HAZARDOUS COMBUSTION PRODUCTS:</b>	Decomposition and combustion materials may be toxic. Burning may produce carbon monoxide and unidentified organic compounds.
<b>CONDITIONS OF FLAMMABILITY:</b>	Heat, sparks, or flame.
<b>EXTINGUISHING MEDIA:</b>	Carbon dioxide, regular foam, dry chemical, water spray, or water fog.

**SAFETY-KLEEN PREMIUM SOLVENT**  
**SAFETY-KLEEN PREMIUM GOLD SOLVENT (VIRGIN AND RECYCLED)**  
**MATERIAL SAFETY DATA SHEET FOR USA AND CANADA**


**NFPA 704**

**HAZARD IDENTIFICATION:**

This information is intended solely for the use by individuals trained in this system.

HEALTH HAZARD  
(BLUE)

FIRE HAZARD  
(RED)



SPECIFIC  
HAZARD  
(WHITE)

REACTIVITY  
(YELLOW)

**FIRE FIGHTING  
INSTRUCTIONS:**

Keep storage containers cool with water spray. A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

**FIRE AND EXPLOSION  
HAZARDS:**

Vapor explosion hazard indoors, outdoors, or in sewers. Vapors may travel to ignition source and flashback. Vapors will spread along the ground and collect in low or confined areas. Run-off to sewer may create a fire hazard. Heated containers may rupture or be thrown into the air. "Empty" containers may retain residue and can be dangerous. Products are not sensitive to mechanical impact. Products may be sensitive to static discharge, which could result in fire or explosion.

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Wear protective equipment and provide engineering controls as specified in **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. A vapor suppressing foam may be used to reduce vapors. Contain spill away from surface water and sewers. Contain spill as a liquid for possible recovery, or sorb with compatible sorbent material and shovel with a clean, sparkproof tool into a sealable container for disposal.

Additionally, for large spills: Water spray may reduce vapor, but may not prevent ignition in closed spaces. Dike far ahead of liquid spill for collection and later disposal.



**SAFETY-KLEEN PREMIUM SOLVENT**  
**SAFETY-KLEEN PREMIUM GOLD SOLVENT (VIRGIN AND RECYCLED)**  
**MATERIAL SAFETY DATA SHEET FOR USA AND CANADA**

---

**SECTION 7: HANDLING AND STORAGE**

- HANDLING:** Keep away from heat, sparks, or flame. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean, sparkproof tools and explosion-proof equipment. When transferring product, metal containers, including trucks and tank cars, should be grounded and bonded. Do not breathe vapor or mist. Use in a well ventilated area. Avoid contact with eyes, skin, clothing, and shoes. Do not smoke while using this product.
- SHIPPING AND STORING:** Keep container tightly closed when not in use and during transport. Store containers in a cool, dry place. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Keep containers away from heat, flame, sparks, static electricity, or other sources of ignition. Empty product containers may retain product residue and can be dangerous. See **SECTION 14: TRANSPORTATION INFORMATION** for Packing Group information.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

- ENGINEERING CONTROLS:** Provide general ventilation needed to maintain concentration of vapor or mist below applicable exposure limits. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below applicable exposure limits. Where explosive mixtures may be present, equipment safe for such locations should be used.

**PERSONAL PROTECTIVE EQUIPMENT**

- RESPIRATORY PROTECTION:** Use NIOSH-certified P- or R- series particulate filter and organic vapor cartridges when concentration of vapor or mist exceeds applicable exposure limits. Protection provided by air purifying respirators is limited. Do not use N-rated respirators. Selection and use of respiratory protective equipment should be in accordance in the USA with OSHA General Industry Standard 29 CFR 1910.134; or in Canada with CSA Standard Z94.4.
- EYE PROTECTION:** Where eye contact is likely, wear chemical goggles; contact lens use is not recommended.

**SAFETY-KLEEN PREMIUM SOLVENT**  
**SAFETY-KLEEN PREMIUM GOLD SOLVENT (VIRGIN AND RECYCLED)**  
**MATERIAL SAFETY DATA SHEET FOR USA AND CANADA**

---

**SKIN PROTECTION:** Where skin contact is likely, wear neoprene, nitrile, or equivalent protective gloves; use of natural rubber or equivalent gloves is not recommended.

To avoid prolonged or repeated contact with products where spills and splashes are likely, wear appropriate chemical-resistant faceshield, boots, apron, coveralls, long sleeve shirts, or other protective clothing.

**PERSONAL HYGIENE:** Use good personal hygiene. Wash thoroughly with soap and water after handling product and before eating, drinking, or using tobacco products. Clean affected clothing, shoes, and protective equipment before reuse. Discard affected clothing, shoes, and/or protective equipment if they cannot be thoroughly cleaned. Discard leather articles, such as shoes, saturated with this product.

**OTHER PROTECTIVE EQUIPMENT:** Where spills and splashes are likely, facilities storing or using these products should be equipped with an emergency eyewash and shower, both equipped with clean water, in the immediate work area.

<b>SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES</b>
--

**PHYSICAL STATE, APPEARANCE, AND ODOR:** Liquid, clear, colorless to pale yellow, mild hydrocarbon odor.

**ODOR THRESHOLD:** 30 ppm (based on Stoddard Solvent)

**MOLECULAR WEIGHT:** Not available.

**SPECIFIC GRAVITY:** 0.77 to 0.80 at 60°F (15.6°C) (water = 1)

**DENSITY:** 6.4 to 6.7 LB/US gal (770 to 800 g/l)

**VAPOR DENSITY:** 5 (air = 1) (approximately)

**VAPOR PRESSURE:** 0.2 mm Hg at 68°F (20°C) (approximately)  
0.6 mm Hg at 100°F (37°C) (approximately)

**BOILING POINT:** 350°F (177°C) (initial)

**FREEZING/MELTING POINT:** -45°F (-43°C) (maximum)

**pH:** Not applicable.

**EVAPORATION RATE:** 0.1 (butyl acetate = 1) (based on Stoddard Solvent)

**SAFETY-KLEEN PREMIUM SOLVENT**  
**SAFETY-KLEEN PREMIUM GOLD SOLVENT (VIRGIN AND RECYCLED)**  
**MATERIAL SAFETY DATA SHEET FOR USA AND CANADA**

---

**SOLUBILITY IN WATER:** Insoluble.

**FLASH POINT:** 148°F (64°C) (approximately) Tag Closed Cup

**FLAMMABLE LIMITS IN AIR:** **LOWER:** 0.7 VOL% (minimum) **UPPER:** 5 VOL% (maximum)

**AUTOIGNITION TEMPERATURE:** 480°F (249°C) (minimum)

**SECTION 10: STABILITY AND REACTIVITY**

**STABILITY:** Stable under normal temperatures and pressures. Avoid heat, sparks, or flame.

**INCOMPATIBILITY:** Avoid acids, alkalies, oxidizing agents, reducing agents, or reactive halogens.

**REACTIVITY:** Polymerization is not known to occur under normal temperature and pressures. Not reactive with water.

**HAZARDOUS DECOMPOSITION PRODUCTS:** None under normal temperatures and pressures. See also **SECTION 5: HAZARDOUS COMBUSTION PRODUCTS.**

**SECTION 11: TOXICOLOGICAL INFORMATION**

**SENSITIZATION:** Based on best current information, there is no known human sensitization associated with this product.

**MUTAGENICITY:** Based on best current information, there is no known mutagenicity associated with this product.

**CARCINOGENICITY:** Based on best current information, there is no known carcinogenicity as categorized by ACGIH A1 or A2 substances; as categorized by IARC Group 1, Group 2A, or Group 2B agents; or as listed by NTP as either known carcinogens or substances for which there is limited evidence of carcinogenicity in humans or sufficient evidence of carcinogenicity in experimental animals.

Also see **SECTION 15: CALIFORNIA.**



**SAFETY-KLEEN PREMIUM SOLVENT**  
**SAFETY-KLEEN PREMIUM GOLD SOLVENT (VIRGIN AND RECYCLED)**  
**MATERIAL SAFETY DATA SHEET FOR USA AND CANADA**

---

**REPRODUCTIVE TOXICITY:** Based on best current information, there is no known reproductive toxicity associated with this product.

Also see **SECTION 15: CALIFORNIA.**

**TERATOGENICITY:** Based on best current information, there is no known teratogenicity associated with this product.

**TOXICOLOGICALLY SYNERGISTIC PRODUCT(S):** Based on best current information, there are no known toxicologically synergistic products associated with this product.

### **SECTION 12: ECOLOGICAL INFORMATION**

**ECOTOXICITY:** A Static Acute Bioassay as per California Department of Fish and Game WPCL was done using fathead minnows and up to 750 ppm of the products in water. The material passed the bioassay.

**OCTANOL/WATER PARTITION COEFFICIENT:** Not available.

**VOLATILE ORGANIC COMPOUNDS:** 100 WT%; 6.4 to 6.7 LB/US gal; 770 to 800 g/l  
As per 40 CFR Part 51.100(s).  
Non-Photochemically Reactive  
VOC Vapor Pressure Approx 0.2 mmHg @20°C

### **SECTION 13: DISPOSAL CONSIDERATIONS**

**DISPOSAL:** Dispose in accordance with federal, state, provincial, and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste. Contact Safety-Kleen regarding proper recycling or disposal.

**USEPA WASTE CODE(S):** Not regulated.  
Based on available data, this information applies to the product as supplied to the user. Processing, use, or contamination by the user may change the waste code applicable to the disposal of this product.

**SAFETY-KLEEN PREMIUM SOLVENT**  
**SAFETY-KLEEN PREMIUM GOLD SOLVENT (VIRGIN AND RECYCLED)**  
**MATERIAL SAFETY DATA SHEET FOR USA AND CANADA**

**SECTION 14: TRANSPORT INFORMATION**

**DOT:** **Bulk Packages (>119 Gallons):**  
**Shipping Name:** Combustible liquid, n.o.s. (petroleum naphtha) **UN/NA**  
**#:** NA1993. **Hazard Class:** Combustible liquid. **Packing Group:** III  
**Required Placards:** Class 3, NA1993

**Non-bulk Packages (<120 Gallons):**  
**Shipping Name:** Cleaning compounds (Petroleum naphtha) (Not US  
DOT regulated). **UN/NA #:** None. **Hazard Class:** None **Packing**  
**Group:** None **Required Label(s):** None

**TDG:** **Shipping Name:** Non-regulated goods.

**EMERGENCY RESPONSE** 128  
**GUIDE NUMBER:** Reference *North American Emergency Response Guidebook*

**SECTION 15: REGULATORY INFORMATION**

**USA REGULATIONS**

**SARA SECTIONS 302 AND 304:** Based on the ingredients listed in **SECTION 2**, this product does not contain any "extremely hazardous substances" listed pursuant to Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) Section 302 or Section 304 as identified in 40 CFR Part 355, Appendix A and B.

**SARA SECTIONS 311 AND 312:** This product poses the following health hazards as defined in 40 CFR Part 370 and are subject to the requirements of sections 311 and 312 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA):  
Immediate (Acute) Health Hazard  
Delayed (Chronic) Health Hazard  
Fire Hazard

**SARA SECTION 313:** This product does not contain "toxic" chemicals subject to the requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372.

**CERCLA:** Based on the ingredient listed in **SECTION 2**, this product does not contain any "hazardous substances" listed pursuant to the Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA) in 40 CFR Part 302, Table 302.4.

**SAFETY-KLEEN PREMIUM SOLVENT**  
**SAFETY-KLEEN PREMIUM GOLD SOLVENT (VIRGIN AND RECYCLED)**  
**MATERIAL SAFETY DATA SHEET FOR USA AND CANADA**

---

**TSCA:** The component of this product is listed on, or is automatically included as "naturally occurring chemical substances" on, or is exempted from the requirement to be listed on, the TSCA Inventory.

**CALIFORNIA:** This product may contain a detectable amount of benzene CAS 71-43-2, p-dichlorobenzene CAS 106-46-7, ethylbenzene CAS 100-41-4, and naphthalene CAS 91-20-3. **WARNING:** These chemicals are known to the State of California to cause cancer.

This product may contain a detectable amount of benzene CAS 71-43-2 and toluene CAS 108-88-3. **WARNING:** These chemicals are known to the State of California to cause birth defects or other reproductive harm.

**CANADIAN REGULATIONS**

This product have been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all information required by the CPR.

**WHMIS:** Class B3 - Combustible Liquid  
Class D2B - Irritating to eyes and skin.

**CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA):** The component of this product is listed on, or is automatically included as "substance occurring in nature" on, or is exempted from the requirements to be listed on, the Canadian Domestic Substances List (DSL).

**SECTION 16. OTHER INFORMATION**

**REVISION INFORMATION:** Section 5, Section 9, Autoignition Temperature.

**LABEL/OTHER INFORMATION:** These products are United States Department of Agriculture (USDA) approved and ETL classified.

---

User assumes all risks incident to the use of this (these) product(s). To the best of our knowledge, the information contained herein is accurate. However, Safety-Kleen assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either express or implied, or merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to information or the product to which information refers. The data contained on this sheet apply to the product(s) as supplied to the user.

